

Chemical Name: Contact Cement

Manufacturer: Ace

Container size: .473L

Location: VLA

Disposal: Place empty container in trash.

04/21/03

AVON, OH 44011

TELEPHONE: (440) 937-7000

MATERIAL SAFETY DATA SHEET Page 01 of 05

ACE ALL-PURPOSE CONTACT CEMENT 50-08866

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: ACE ALL-PURPOSE CONTACT CEMENT

Item No.: 50-08866

Part No.:

Product Type: Contact Cement

2. COMPOSITION, INFORMATION ON INGREDIENTS

Ingredients	CAS No.	용
CYCLOHEXANE*	110-82-7	40-60
METHYL ETHYL KETONE*	78-93-3	10-20
Neoprene	9010-98-4	10-20
n-PROPYL ACETATE	109-60-4	5-10
Proprietary Resin Compound	Proprietary	5-10
Rosin	068083-03-4	1-5

^{*} This component is listed as a SARA Section 313 Toxic Chemical.

Ingredients which have exposure limits

Exposure Limits (TWA) Ingredients	ACGIH (TLV)	OSHA (PEL)	OTHER
CYCLOHEXANE	300 ppm TWA 1030 mg/m3	300 ppm TWA 1030 mg/m3	None
METHYL ETHYL KETONE	200 ppm TWA 590 mg/m3	200 ppm TWA 590 mg/m3	None
n-PROPYL ACETATE	200 ppm TWA 835 mg/m3	200 ppm TWA 840 mg/m3	None
Exposure Limits (STEL) Ingredients	ACGIH (TLV)	OSHA (PEL)	
METHYL ETHYL KETONE	300 ppm 885 mg/m3	300 ppm 885 mg/m3	
n-PROPYL ACETATE	250 ppm 1040 mg/m3	250 ppm 1050 mg/m3	

3. HAZARDS IDENTIFICATION

Toxicity: May cause eye, skin and respiratory tract irritation.

May cause drying or defatting of skin leading to

dermatitis.

Inhalation of vapors may cause central nervous effects including dizziness, weakness, nausea, and headache. Ingestion may cause irritation, nausea, vomiting and diarrhea.

04/21/03 HENKEL CONSUMER ADHESIVES

AVON, OH 44011

TELEPHONE: (440) 937-7000

MATERIAL SAFETY DATA SHEET Page 02 of 05

Product Name: ACE ALL-PURPOSE CONTACT CEMENT

Item No.: 50-08866

3. HAZARDS IDENTIFICATION (continued)

Overexposure to methyl ethyl ketone may cause lung,

kidney and liver damage.

Primary Routes of Entry: Skin, eye, inhalation, ingestion

Signs and Symptoms

Eye, skin, and respiratory tract irritation. of Exposure: Dizziness, weakness, headaches and nausea.

Existing Conditions

Aggravated by Exposure: Skin disorders

Literature Referenced Carcinogen Ingredients Target Organ and Other Health Effects NTP IARC OSHA CYCLOHEXANE CNS IRR NO NO NO METHYL ETHYL KETONE NO N/A NO CNS IRR NTO NO N/A NO Neoprene n-PROPYL ACETATE CNS IRR NO NO NO

Proprietary Resin Compound No Data NO NO Rosin No Data NO NO NO ______

Abbreviations

N/A Not Applicable CNS Central nervous system IRR Irritant NTO No Target Organs

4. FIRST AID MEASURES

Do NOT induce vomiting unless directed to do so by a Ingestion:

physician. Never give anything by the mouth to an

unconscious person. Get medical attention immediately. Remove to fresh air. If

Inhalation:

breathing is difficult, administer oxygen. If not

breathing, give artificial respiration. If breathing is

difficult, give oxygen. Get medical attention

immediately.

Skin Contact: Remove contaminated clothing, wash immediately with soap

and water. Wash contaminated clothing thoroughly before

reuse. If irritation persists, obtain medical

attention.

Eye Contact: Flush thoroughly with water for at least 15

minutes. If irritation persists, obtain medical

attention.

5. FIRE FIGHTING MEASURES

< 0°F Flash Point:

Recommended

Extinguishing Agents: Water fog, carbon dioxide, foam, or dry chemical.

Special Firefighting

Procedures: Water spray can be used to cool containers. A solid HENKEL CONSUMER ADHESIVES 04/21/03

AVON, OH 44011

TELEPHONE: (440) 937-7000

MATERIAL SAFETY DATA SHEET Page 03 of 05

Product Name: ACE ALL-PURPOSE CONTACT CEMENT

Item No.: 50-08866

5. FIRE FIGHTING MEASURES (continued)

stream of water directed on hot and/or burning material

may cause violent frothing.

Hazardous Products formed

by Fire or Thermal Decomp Oxides of carbon, hydrocarbons, chlorine compounds.

Unusual Fire or

Explosion Hazards: None

Explosive Limits:

(% by volume in air)Lower Not available (% by volume in air)Upper Not available

6. ACCIDENTAL RELEASE MEASURES

Steps to be taken in case

of spill or leak: Eliminate all sources of ignition. Ventilate area.

Clean up spills immediately. Soak up with an inert absorbent. Clean residual material with soap and water.

Placed in a closed container until disposal.

7. HANDLING AND STORAGE

Safe Storage: Keep in a cool and well ventilated area. Keep container

closed tightly closed and sealed until ready to use.

(Contact Loctite Customer Service 1-800-243-4874 for shelf life information)

Handling: Keep away from heat, sparks, and flame. Keep container

closed. Use only with adequate ventilation.

8. EXPOSURE CONTROLS, PERSONAL PROTECTION

Eyes: Chemical splash goggles or safety glasses with side

shields.

Skin: Use chemical resistant, impermeable gloves.

Ventilation: Use local exhaust ventilation to maintain airborne

exposure levels below established exposure limits.

Respiratory Use NIOSH approved respirator as required to prevent

overexposure.

See Section 2 for Exposure Limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Yellowish Liquid

Odor: Solvent

Boiling Point: More than 300°F pH: Does not apply

Solubility in Water: Insoluble Specific Gravity 0.827

Volatile Organic Compound

(EPA Method 24) Not available Vapor Pressure: Not available

HENKEL CONSUMER ADHESIVES 04/21/03

AVON, OH 44011

TELEPHONE: (440) 937-7000

MATERIAL SAFETY DATA SHEET Page 04 of 05

Product Name: ACE ALL-PURPOSE CONTACT CEMENT

Item No.: 50-08866

9. PHYSICAL AND CHEMICAL PROPERTIES (continued)

Vapor Density: Not available

Evaporation Rate

(Ether = 1) More than butyl acetate

10. STABILITY AND REACTIVITY

Stability: Stable

Hazardous Polymerization: Will not occur

Incompatibility: Strong oxidizing agents.

Conditions to Avoid: Keep away from heat, spark and flame.

Hazardous Decomposition

Products (non-thermal): None

11. TOXICOLOGICAL INFORMATION

See Section 3.

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended methods of

disposal: Dispose of following EPA and local regulations. Use of

an approved hazardous waste disposal contractor is

recommended.

EPA Hazardous Waste

Number D001/D035 - Hazardous waste per 40CFR 261.21 and

a TCLP waste per 261.24/Methyl Ethyl Ketone.

14. TRANSPORTATION INFORMATION

DOT (49 CFR 172)

Domestic Ground Transport

Proper Shipping Name: Consumer Commodity (Not more than one liter);

Adhesives, containing a flammable liquid (More than one

liter)

Hazard Class or

Division: ORM-D (Not more than one liter);

Class 3, Packing Group II (More than one liter)

Identification Number: None (Not more than one liter);

UN 1133 (More than one liter)

Marine Pollutant: None

IATA

Proper Shipping Name: Consumer Commodity (Not more than 500 ml);

Adhesives, containing a flammable liquid (More than 500

ml)

Class or Division: Class 9 (Not more than 500 ml);

AVON, OH 44011

TELEPHONE: (440) 937-7000

MATERIAL SAFETY DATA SHEET Page 05 of 05

Product Name: ACE ALL-PURPOSE CONTACT CEMENT

Item No.: 50-08866

14. TRANSPORTATION INFORMATION (continued)

Class 3, Packing Group II (More than 500 ml)

UN or ID Number: ID 8000 (Not more than 500 ml);

UN 1133 (More than 500 ml)

15. REGULATORY INFORMATION

CA Proposition 65: WARNING: This product contains chemicals known to

the State of California to cause cancer.

16. OTHER INFORMATION

Estimated NFPA(R) Code:

Health Hazard: 2
Fire Hazard: 3
Reactivity Hazard: 0

Reactivity Hazard: 0
Specific Hazard: Does not apply

Estimated HMIS(R) Code:

Health Hazard: 2*
Flammability Hazard: 3
Reactivity Hazards: 0

Personal Protection: See Section 8.

NFPA is a registered trademark of the National Fire Protection Assn. HMIS is a registered trademark of the National Paint and Coatings Assn.

(24hr.) Phone: (440) 937-7000