



Chemical Name: Satin Stainless Steel Cleaner and Polish

Manufacturer: Allstar

Container size: 16oz.

Location: VLA

Disposal: Place empty container in the trash.

AMREP INC -- ALL STAR STAINLESS STEEL CLEANER -- 7930-00N020079

=====
Product Identification
=====

Product ID:ALL STAR STAINLESS STEEL CLEANER
MSDS Date:07/01/1989
FSC:7930
NIIN:00N020079
MSDS Number: BLVLG
=== Responsible Party ===
Company Name:AMREP INC
Address:990 INDUSTRIAL PARK DR
City:MARIETTA
State:GA
ZIP:30062
Country:US
Info Phone Num:404-386-3083
Emergency Phone Num:404-386-3083 800-424-9300(CHEMTREC)
Preparer's Name:TMJ/STN
CAGE:3V338
=== Contractor Identification ===
Company Name:AMREP INC
Address:990 INDUSTRIAL PK DR
Box:City:MARIETTA
State:GA
ZIP:30062-2433
Country:US
Phone:404-422-2071
CAGE:3V338

=====
Composition/Information on Ingredients
=====

Ingred Name:NAPHTHALENE; (PETROLEUM DISTILLATES)
CAS:91-20-3
RTECS #:QJ0525000
Fraction by Wt: 15%.0
OSHA PEL:10 PPM; 15 PPM STEL
ACGIH TLV:10 PPM; 15 PPM STEL
EPA Rpt Qty:100 LBS
DOT Rpt Qty:100 LBS

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 8.0%
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ETHANE, 1,1,1-TRICHLORO-; (METHYL CHLOROFORM)
CAS:71-55-6
RTECS #:KJ2975000
Fraction by Wt: 40.0%
OSHA PEL:350 PPM;450 PPM STEL
ACGIH TLV:350 PPM;450 PPM STEL
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS
Ozone Depleting Chemical:1

Ingred Name:ETHYLENE, TETRACHLORO-; (PERCHLOROETHYLENE)
CAS:127-18-4
RTECS #:KX3850000
Fraction by Wt: 10.0%
OSHA PEL:100 PPM
ACGIH TLV:25PPM/100,A3 STEL;94
EPA Rpt Qty:100 LBS
DOT Rpt Qty:100 LBS

Ingred Name:ISOBUTANE (75-28-5)/PROPANE (74-98-6) BLEND. LIMITS AS
PROPANE.
Fraction by Wt: 15%
OSHA PEL:1000 PPM
ACGIH TLV:SIMPLE ASPHYXIAN

=====
Hazards Identification
=====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO
Health Hazards Acute and Chronic:ACUTE:INHAL: EXCESSIVE INHAL OF VAPS
CAN BE HARMFUL & MAY CAUSE HDCH/DIZZ/ASPHYXIA/ANESTHETIC EFTS &
POSSIBLE UNCON. EYE:MILD IRRIT. SKIN:IRRIT, MILD DEFATTING OF SKIN.
INGEST:POSSIBLE CHEM PNEUM IF A SPIRATED INTO LUNGS. NAUSEA.
CHRONIC:EFTS DUE TO EXCESSIVE EXPOSURE TO RAW MATERIALS OF MIXTURE.
(SEE EFTS OF OVEREXP)

Explanation of Carcinogenicity:PERCHLOROETHYLENE: IARC GROUP 2B, NTP
KNOWN ANIMAL CARCINOGEN/SUSPECTED HUMAN CARCINOGEN.

Effects of Overexposure:HLTH HAZ:HAS SHOWN LIVER & TOXIC EFTS IN TEST
ANIMALS. CHLOROCARBON MATL HAVE PRDCD/SENSIT OF MYOCARDIUM TO
EPINEPHRINE IN LAB ANIMALS & COULD HAVE SIMILAR EFT IN HUMANS.
ADRENOMIMETICS(E.G., EPINEPHR INE) MAY BE CONTRAINDICATED EXCEPT
FOR LIFE- SUSTAINING USES IN HUMANS ACUTELY/CHRONICALLY EXPOS TO
CHLOROCARBONS.

Medical Cond Aggravated by Exposure:MAY AGGRAVATE EXISTING EYE, SKIN,
OR UPPER RESPIRATORY CONDITIONS.

=====
First Aid Measures

First Aid:EYE: FLUSH WITH WATER FOR AT LEAST 15 MIN. IF IRRITATED, SEE
PHYS. SKIN: WASH WITH SOAP AND WATER. IF IRRITATED, SEE PHYS.
INHAL: REMOVE TO FRESH AIR. RESUSCITATE IF NECESSARY. GET MED AID.
INGEST: DO NOT INDUCE VOMIT. GET MED ATTN IMMED.

=====
Fire Fighting Measures

Extinguishing Media:FOAM, DRY CHEMICAL, CARBON DIOXIDE.
Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED PRESSURE DEMAND SCBA
AND FULL PROTECTIVE EQUIPMENT .
Unusual Fire/Explosion Hazard:DO NOT EXPOSE AEROSOLS TO TEMPERATURES
ABOVE 130F OR THE CONTAINER MAY RUPTURE. THERMAL DECOMPOSITION
PRODUCTS MAY INCLUDE HCL & PHOSGENE .

=====
Accidental Release Measures

Spill Release Procedures:ABSORB WITH SUITABLE MEDIUM. INCINERATE OR
LANDFILL ACCORDING TO LOCAL, STATE, OR FEDERAL REGULATIONS. DO NOT
FLUSH TO SEWER.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
Handling and Storage

Handling and Storage Precautions:DO NOT PUNCTURE OR INCINERATE
CONTAINERS. DO NOT STORE AT TEMPERATURES ABOVE 130F.
Other Precautions:AVOID FOOD CONTAM. KEEP OUT OF REACH OF CHILDREN.
REMOVE IGNIT SOURCES. AVOID BRTHG VAPORS. NO SMOKING IN AREA OF
USE. DO NOT USE IN GEN VICINITY OF ARC WELDING/OPEN FLAMES/HOT
SURF. HEAT/UV RADIATION MAY CAUSE FORM OF HCL/PHOSGENE.

=====
Exposure Controls/Personal Protection

Respiratory Protection:IF VAPOR CONC EXCEEDS TLV, USE RESPIRATOR
APPROVED BY NIOSH/MSHA/U.S. BUREAU OF MINES FOR ORGANIC VAPOR.
Ventilation:ADEQUATE VENTILATION TO KEEP VAPOR CONCENTRATION BELOW TLV.
Protective Gloves:NEOPRENE GLOVES.
Eye Protection:CHEMICAL WORKERS GOGGLES .
Other Protective Equipment:NONE.
Work Hygienic Practices:WASH WITH SOAP AND WATER BEFORE HANDLING FOOD.
REMOVE CONTAMINATED CLOTHING.
Supplemental Safety and Health
NONE SPECIFIED BY MANUFACTURER.

=====
Physical/Chemical Properties

Vapor Pres:60PSIG
Spec Gravity:1.015
Solubility in Water:INSOLUBLE
Appearance and Odor:SPRAY MIST WITH LEMON FRAGRANCE.

=====
Stability and Reactivity Data

Stability Indicator/Materials to Avoid:YES
ALKALIES, STRONG OXIDIZERS, ACIDS.
Stability Condition to Avoid:OPEN FLAME, WELDING ARCS, HEAT, SPARKS.
Hazardous Decomposition Products:CO, CO2, HYDROGEN CHLORIDE, SMALL
AMOUNTS OF CHLORINE & PHOSGENE.

=====
Disposal Considerations

Waste Disposal Methods:AEROSOL CANS WHEN VENTED TO ATMOSPHERIC PRESSURE

THROUGH NORMAL USE, POSE NO DISPOSAL HAZARD. DISPOSE OF IN
ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS .

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.