

Chemical Name: Loosen-It

Manufacturer: CarQuest

Container Size: 9 oz.

Location: VLA

Disposal: Place empty container in trash. Give partial or full container to safety officer.



Section 1: Product & Company Identification

Product Name: Carquest Loosen-It[™] (aerosol)

Product Number (s): 1050, 1050C (CRC Part# 09683)

Manufactured By: CRC Industries, Inc. 885 Louis Drive Warminster, PA 18974 www.crcindustries.com

 General Information
 (215) 674-4300

 Technical Assistance
 (800) 521-3168

 Customer Service
 (800) 272-4620

 24-Hr Emergency (CHEMTREC)
 (800) 424-9300

Section 2: Hazards Identification

Emergency Overview

Appearance & Odor: Light amber liquid, petroleum solvent odor

DANGER

Flammable. Harmful or Fatal if Swallowed. Contents Under Pressure.

As defined by OSHA's Hazard Communication Standard, this product is hazardous.

Potential Health Effects:

EYE:	May cause mild eye irritation. Symptoms include stinging, tearing and redness.		
SKIN:	Can cause skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying, and cracking of the skin.		
INHALATION:	Expected to have a low degree of toxicity by inhalation. Breathing concentrated vapors may be harmful. Symptoms of overexposure include irritation of the nose and throat, headache, dizziness, drowsiness, loss of coordination and other signs of central nervous system depression.		
INGESTION:	Low degree of toxicity by ingestion. May cause irritation of digestive tract, nausea and vomiting. Main hazard is aspiration of material into lungs during swallowing or vomiting. This can lead to lung inflammation and damage.		
CHRONIC EFFECTS:	Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.		
TARGET ORGANS:	Kidneys, central nervous system.		
Medical Conditions Aggra	vated by Exposure: skin disorders, respiratory disorders		

See Section 11 for toxicology and carcinogenicity information on product ingredients.

COMPONENT	CAS NUMBER	% by Wt.
Stoddard solvent	8052-41-3	45 - 55
Hydrotreated light distillates	64742-47-8	35 - 45
Solvent refined heavy paraffinic distillates	64741-88-4	5 - 10
Oleic acid	112-80-1	1 - 5
Carbon dioxide	124-38-9	1 - 5

Section 3: Composition/Information on Ingredients

Section 4: First Aid Measures

Eye Contact:	Immediately flush with plenty of water for 15 minutes. Call a physician if irritation persists.
Skin Contact:	Remove contaminated clothing and wash affected area with soap and water. Call a physician if irritation persists. Wash contaminated clothing prior to re-use.
Inhalation:	Remove person to fresh air. Keep person calm. If not breathing, give artificial respiration. If breathing is difficult give oxygen. Call a physician.
Ingestion:	Do not induce vomiting. Contact a physician immediately. If victim is drowsy or unconscious, place individual on the left side with head down.
Note to Physicians:	This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity when deciding whether to induce vomiting.

Section 5: Fire-Fighting Measures

Flammable Properties:	This product is flammable in accordance with aerosol flammability definitions (16 CFR 1500.3(c)(6)).			
Flash Point: Autoignition Temperature:	109 F (TCC) ND	Upper Explosive Limit: Lower Explosive Limit:	6.0 (est) 1.0 (est)	
Suitable Extinguishing Media:	Foam, carbon dioxide, dry chemical; Class B fire extinguishers			
Products of Combustion:	Oxides of carbon			
Protection of Fire-Fighters:	Firefighters should wear self-contained, NIOSH-approved breathing apparatus for protection against suffocation and possible toxic decomposition products. Proper eye and skin protection should be provided. Use water spray to keep fire-exposed containers cool and to knock down vapors which may result from product decomposition.			

Section 6: Accidental Release Measures

Personal Precautions: Use personal protection recommended in Section 8.

Environmental Precautions: Take precautions to prevent contamination of ground and surface waters. Do not flush into sewers or storm drains.

Methods for Containment & Clean-up: Dike area to contain spill. Ventilate the area with fresh air. If in confined space or limited air circulation area, clean-up workers should wear appropriate respiratory protection. Recover or absorb spilled material using an absorbent designed for chemical spills. Place used absorbents into proper waste containers.

Section 7: Handling and Storage

Handling Procedures:	Do not use near sources of ignition. Do not use on energized equipment. Use with proper ventilation. Wash hands after use and before handling food.		
Storage Procedures:	Store in a cool dry area out of direct sunlight. Aerosol cans must be maintained below 120 F to prevent cans from rupturing.		
Aerosol Storage Level:	III		

Section 8: Exposure Controls/Personal Protection

Exposure Guidelines:

	OS	SHA	AC	GIH	0	THER	
COMPONENT	TWA	STEL	TWA	STEL	TWA	SOURCE	UNIT
Stoddard solvent	500	NE	100	NE	NE		ppm
Hydrotreated light distillates	NE	NE	NE	NE	NE		
Solvent refined heavy paraffinic distillates	NE	NE	NE	NE	NE		
Oleic acid	NE	NE	NE	NE	NE		
Carbon dioxide	5000	NE	5000	30000	NE		ppm
N.E. – Not Established (c) – ceiling (s) – skin (v) – vacated							

Engineering Controls:	Area should have ventilation to provide fresh air. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at the source, preventing dispersion into the general work area. Use mechanical means if necessary to maintain vapor levels below the exposure guidelines. If working in a confined space, follow applicable OSHA regulations.
Respiratory Protection:	None required for normal work where adequate ventilation is provided. If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies.
Eye/face Protection:	For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear splash-proof goggles.

Product Name: Carquest Loosen-It[™] (aerosol) Product Number (s): 1050, 1050C (CRC Part# 09683)

Skin Protection:

Use protective gloves such as nitrile or neoprene. Also, use full protective clothing if there is prolonged or repeated contact of liquid with skin.

Section 9: Physical and Chemical Properties

Physical State: liquid			
Color: light amber			
Odor: petroleum solvent			
Specific Gravity: 0.790			
Initial Boiling Point: 300 F			
Freezing Point: ND			
Vapor Pressure: ND			
Vapor Density: > 4	(air = 1)		
Evaporation Rate: < 1	(butyl acetate = 1)		
Solubility: insoluble in water			
pH: NA			
Volatile Organic Compounds	<u>wt %</u> : 48.4	<u>q/L</u> : 382.4	<u>lbs./gal:</u> 3.19

Section 10: Stability and Reactivity

Stability:	Stable		
Conditions to Av	void:	Sources of ig	nition; temperature extremes
Incompatible Ma	aterials:	Strong oxidiz	ing agents
Hazardous Deco	omposition F	Products:	oxides of carbon
Possibility of Ha	zardous Re	actions:	No

Section 11: Toxicological Information

Long-term toxicological studies have not been conducted for this product. The following information is available for components of this product.

ACUTE EFFECTS

<u>Component</u>	Test	<u>Result</u>	<u>Route</u>	<u>Species</u>
Hydrotreated light distillate	LD50	> 5 g/kg	Oral	Rat
Hydrotreated light distillate	LD50	> 2 g/kg	Dermal	Rabbit
Hydrotreated light distillate	LC50	> 5 mg/L/4H	Inhalation	Rat

CHRONIC EFFECTS

Carcinogenicity:

	<u>Component</u>	Result
OSHA:	None listed	
IARC:	None listed	
NTP:	None listed	

Mutagenicity: No information available

Other:

Section 12: Ecological Information

None

Ecological studies have not been conducted for this product. The following information is available for components of this product.

Ecotoxicity:	No information available
Persistence / Degradability:	No information available
Bioaccumulation / Accumulation:	No information available
Mobility in Environment:	No information available

Section 13: Disposal Considerations

Disposal: The dispensed liquid product is a RCRA hazardous waste for the characteristic of ignitability with a waste code of D001. (See 40 CFR Part 261.20 – 261.33) Aerosol containers should be emptied and depressurized before disposal. Empty containers may be recycled.

All disposal activities must comply with federal, state and local regulations. Local regulations may be more stringent than state or national requirements.

Section 14: Transport Information

Proper shipping description:

US DOT (ground): Consumer Commodity, ORM-D

Special Provisions: None

Section 15: Regulatory Information

U.S. Federal

Toxic Substances Control Act (TSCA):

All ingredients are either listed on the TSCA inventory or are exempt.

Comprehensive Environmental Response, Compensation and Liability Act (CERCLA):

Reportable Quantities (RQ's) exist for the following ingredients: None

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Superfund Amendments Reauthorization Act (SARA) Title III:

Section 302 Extremely Hazardous Substances (EHS): None

Section 311/312 Hazard Categories:	Fire Hazard	Yes
-	Reactive Hazard	No
	Release of Pressure	Yes

Product Name: Carquest Loosen-It[™] (aerosol) Product Number (s): 1050, 1050C (CRC Part# 09683)

Floudet Mulliber (s). 1050, 10					
	Acute Health Hazard Yes Chronic Health Hazard No				
Section 313 Toxic Chemicals:	cals: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372: None				
Clean Air Act:					
Section 112 Hazardous Air Pollu	utants (HAPs): None				
State Regulations					
California Safe Drinking Water and Toxic Enforcement Act (Prop 65): This product may contain the following chemicals known to the state of California to cause cancer, birth defects or other reproductive harm: None					
State Right to Know:					
New Jersey:8052-41-3, 124-Pennsylvania:8052-41-3, 124-Massachusetts:8052-41-3, 124-Rhode Island :8052-41-3, 124-	-38-9, 112-80-1 -38-9, 112-80-1				
Additional Regulatory Information: This product complies with Consumer Product VOC regulations as a Penetrant.					
Section 16: Other Informat	ion				
	lammability: 2 Reactivity: 0 lammability: 2 Reactivity: 0 PPE: B				
Prepared By: Michelle Rudnick CRC #: 575G Revision Date: 08/15/2007					
Changes since last revision: Se	ection 9: Reduced VOC content				

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label.

CAS:	Chemical Abstract Service	NA:	Not Applicable		
ppm:	Parts per Million	ND:	Not Determined		
TCC:	Tag Closed Cup	NE:	Not Established		
PMCC:	Pensky-Martens Closed Cup	g/L:	grams per Liter		
PPE:	Personal Protection Equipment	lbs./gal:	pounds per gallon		
TWA:	Time Weighted Average	STEL:	Short Term Exposure Limit		
OSHA:	Occupational Safety and Health Administration				
ACGIH	American Conference of Governmental Industrial Hygienists				
NIOSH	National Institute of Occupational Safety & Health				