

Chemical Name: Liquid Wrench Super Lubricant

Manufacturer: Gunk

Container size: 11oz.

Location: VLA

**Disposal:** Place empty container in trash.

# MSDS No.: L704

## I. Basic Information:

Manufacturer: RADIATOR SPECIALTY COMPANY Address: 600 RADIATOR ROAD City, ST Zip: INDIAN TRAIL, NC 28079 Country:

Product Name: UNIVERAL CHAIN LUBE (POUR) MSDS No.: L704

Issue Date: 03/11/2010 Supersedes Date: Not Available

# II. Hazards Identification:

### EMERGENCY OVERVIEW

Danger: Combustible, Harmful for fatal if swallowed, Eye and Skin Irritant,

#### **OSHA Regulatory Status**

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

#### Potential Health Effects

#### Route(s) of Entry:

Eyes, skin, inhalation, ingestion

Health Hazards (Acute and Chronic):

See signs and symptoms below

#### Signs and Symptoms:

Eye Irritant. Skin irritation, defatting and dermatitis on prolonged exposure. Vapors harmful. May cause irritation to lungs, narcosis effects. Harmful if swallowed.

Medical Conditions Generally Aggravated by Exposure:

None known

#### **Other Health Warnings:**

Vomiting and subsequent aspiration into the lungs may lead to chemical pneumonia and pulmonary edema which is a potentially fatal condition.

#### Potential Environmental Effects

Not Available

# **III.** Composition/Information on Ingredients:

Chemical Name	CAS No.	% Range	Trade Secret
1,2,4-Trimethylbenzene	95-63-6	3.0 - 7.0	
Aliphatic Hydrocarbon Solvent	8052-41-3	40.0 - 70.0	
Butene, homopolymer	9003-29-6	10.0 - 30.0	
Ethylbenzene	100-41-4	0.1 - 1.0	
Ethylene/Propylene Co-Polymer	9010-79-1	1.0 - 5.0	
Mesitylene	108-67-8	3.0 - 7.0	
Molybendum, bis carbamodithioate oxo thioxo complexes	906665-74-5	0.1 - 1.0	
laphthenic Petroleum Distillate	64742-52-5	0.1 - 1.0	
Petroleum Oil	64742-65-0	10.0 - 30.0	
Kylene (mixed isomers)	1330-20-7	1.0 - 5.0	
Zinc Compound	19210-06-1	<0.1	

# Contact: Robert Geer Information Telephone Number: 704-684--181 1 Emergency Contact: Rocky Mountain Poison and Drug Center Emergency Telephone Number: 303-623-5716 Emergency Restrictions:

# MSDS No.: L704

## IV. First Aid Measures:

### Emergency and First Aid Procedures:

Eye Contact: Flush eyes with clean water for 15 minutes while lifting eyelids and get prompt medical attention.

Skin Contact: Wash with soap and water thoroughly. If adverse effects persist, get prompt medical attention. Launder contaminated clothing before reuse.

Inhalation: Remove to fresh air. If breathing becomes difficult get prompt medical attention.

Ingestion: DO NOT INDUCE VOMITING! Call Poison Control Center, physician, or hospital emergency room immediately.

#### Note to Physicians:

N/D

## V. Fire Fighting Measures:

#### Suitable Extinguishing Media:

Water Fog, Foam, Carbon Dioxide, Dry Chemical

#### Unsuitable Extinguishing Media:

Do not use forced water stream as this could cause the fire to spread.

#### **Products of Combustion:**

Normal products of combustion: Carbon dioxide, carbon monoxide, smoke, nitrogen and sulfur oxides

#### Protection of Firefighters:

Wear self-contained positive pressure breathing apparatus and protective clothes. Use shield to protect from rupturing and venting containers. At elevated temperatures containers may vent, rupture or burst, even violently

## VI. Accidental Release Measures:

#### Personal Precautions:

Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

#### Environmental Precautions:

Prevent run-off to sewers, streams, or other bodies of water. If run-off occurs, notify proper authorities as required that a spill has occurred. Run off to sewer may create fire or explosion hazard.

#### Methods for Containment:

Dike or contain spill and absorb with inert materials (sand, sawdust, absorbent sweeping compounds, rags, etc).

#### Methods for Cleanup:

Using a non-metalic scoop, place contaminated material into an approved chemical waste container. Where possible, vacuum spilled liquid using an explosion proof vacuum to recover material.

#### Other Information:

All equipment used with handling the concentrate must be grounded. If run-off occurs, notify proper authorities as required that a spill has occurred.

# VII. Handling and Storage:

#### Handling Precautions:

Handling: Use with adequate ventilation and proper protective equipment.

Do not use near fire, sparks, or flame. Contact lenses may cause further damage in case of splash into eye. KEEP AWAY FROM CHILDREN AND ANIMALS!

#### Storage Precautions:

Store in cool, well ventilated area below 120°F away from heat sources.

# VIII. Exposure Controls/Personal Protection:

# **MSDS** No.: L704

Chemical Name	OSHA PEL	ACGIH TLV	Other Limits
Aliphatic Hydrocarbon Solvent	100 ppm	100 ppm	Not Available
Ethylene/Propylene Co-Polymer	N/E	N/E	Not Available
1,2,4-Trimethylbenzene	N/E	25 ppm	Not Available
Mesitylene	N/A	N/A	Not Available
Xylene (mixed isomers)	100 ppm	100 ppm	Not Available
Ethylbenzene	100 ppm	100 ppm	Not Available
Petroleum Oil	5 mg/m3	5 mg/m3	Not Available
Zinc Compound	N/E	N/E	Not Available
Butene, homopolymer	N/E	N/E	Not Available
Naphthenic Petroleum Distillate	5 mg/m3	5 mg/m3	Not Available
Molybendum, bis carbamodithioate oxo thioxo complexes	5 mg/m3	10 mg/m3	Not Available

#### Engineering Controls:

See above Section for applicable exposure limits. Use with adequate ventilation. If TLV is exceeded, wear NIOSH approved respirator.

#### Personal Protective Equipment:

For prolonged exposure wear protective safety glasses, gloves, and apron.

# IX. Physical and Chemical Properties:

Boiling Point: 315°F Boiling Range: Not Available Solubility In Water: Insoluble Flash Point: 110°F Odor Threshold: Not Available Vapor Density (AIR = 1): N/D pH Range: N/A Decomposition Temp: Not Available Lower Explosive Limit: N/D Specific Gravity (H20 = 1): 0.82 Other Information: VOC Content: 54% (Wt)

Melting Point: N/A Freezing Point: Not Available Evaporation Rate (Butyl Acetate = 1): N/D Flash Point Method: TCC Appearance and Odor: Hazy bright yellow with petroleum odor Vapor Pressure (mm Hg.): N/D Partition Coefficient: Not Available Auto-Ignition Temp: Not Available Upper Explosive Limit: N/D

# X. Stability and Reactivity:

## Stability:

Stable

# Conditions to Avoid:

See Incompatible Materials below.

## Incompatible Materials:

Oxidizing agents and acids.

## Hazardous Decomposition Products:

Normal products of combustion: Carbon dioxide, carbon monoxide, smoke, nitrogen and sulfur oxides

#### Possibility of Hazardous Reactions:

Will not occur

MSDS No.: L704

XI. Toxicological Information:

N/D

XII. Ecological Information:

N/D

## XIII. Disposal Considerations:

DISPOSAL: This container may be recycled in a recycling centers when empty. Before offering for recycling, empty the can or bottle by using the product according to the label. If recycling is not available, wrap the empty container and discard in the trash. Do not dump into sewers, on the ground, or into any body of water. Dispose of unused product in accordance with all local, state government and federal laws and regulations

## XIV. Transport Information:

Shipping Name: Petroleum Products, n.o.s. (Aliphatic Petroleum Distillate)

DOT Hazard Class: Class 3

UN/NA#: UN1268

Transportation Information: DOT Hazard Class: ORM-D Shipping Name: Consumer Commodity DOT Subsidiary Hazard Class: Not Available Packing Group: III

The DOT description is provided to assist in the proper shipping classification of this product and may not be suitable for international and air shipping purposes.

ICAO/IATA (US) Shipping Name: Petroleum Products, n.o.s. (Aliphatic Petroleum Distillate) Class: 3 Packaging Group: III UN number: UN1268

International:

ICAO/IATA UN number: UN1268 Shipping Name: Petroleum Products, n.o.s. (Aliphatic Petroleum Distillate) Class: 3 Packaging Group: III

IMDG UN number: UN1268 Shipping Name: Petroleum Products, n.o.s. (Aliphatic Petroleum Distillate) Class: 3 Packaging Group: III EmS: F-E, S-E

## XV. Regulatory Information:

SARA 313 Reportable Chemicals: 1,2,4-Trimethylbenzene (95-63-6) Ethylbenzene (100-41-4) Xylene (1330-20-7) Zinc Dithiophosphate (19210-06-1)

USA TSCA: All components of this material are listed on the US TSCA Inventory.

Warning: This product contains a chemical(s) known to the State of California to cause cancer or birth defects or other reproductive harm.

State RTK Chemicals: Ethylbenzene (100-41-4) Xylene (1330-20-7)

**MSDS** No.: L704

XVI. Other Information:							
Chemical State: Chemical Type: Hazard Category:	Liquid Pure	Gas X Mixture	Solid	NFPA Health	Fire 2 Reactivity 0		
X Acute	X Chronic Pressure	X Fire Reactive			Special		
Additional Manufacturer	<u> Varnings:</u>						
Do not used in confined area without proper ventilation. Contact lenses may cause further damage in case of splash into eye. KEEP AWAY FROM CHILDREN AND ANIMALS!			1	Health			
			2	Flammability			
N/E: Not Established N/D: Not Determined N/A: Not Applicable N/AV: Not Available Additional Product Information:			0	Physical Hazard			
			Н	Pers. Protection			
While Padiator Specialty	Company believe	e this data is acc	urate as of the rev	vision data	we make no warranty with respect to the		

While Radiator Specialty Company believes this data is accurate as of the revision date, we make no warranty with respect to the data and we expressly disclaim all liability for reliance thereon. The data is offered solely for information, investigation, and verification. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this MSDS. The user is responsible for full compliance.