



**Chemical Name:** Fast-Drying Polyurethane

**Manufacturer:** Minwax

**Container Size:** 11.5 oz.

**Location:** VLA

**Disposal:** Place empty container in trash. Give partial or full container to safety officer.

OHIO STATE UNIVERSITY COLLEGE OF BIOLOGICAL SCIENCES MSDS FILE

MINWAX DIV OF EASTMAN KODAK -- MO60370 MINWAX FAST DRYING POLYURETHANE  
CLEAR-ALL - SATIN  
MATERIAL SAFETY DATA SHEET  
FSC: 9160  
NIIN: 00F039162  
Manufacturer's CAGE: 0K1A4  
Part No. Indicator: A  
Part Number/Trade Name: MO60370 MINWAX FAST DRYING POLYURETHANE CLEAR-ALL  
FINISHES

=====  
General Information  
=====

Item Name: SATIN  
Company's Name: MINWAX CO DIV OF EASTMAN KODAK CO  
Company's Street: 15 MERCEDES DRIVE  
Company's P. O. Box: 438  
Company's City: MONTVALE  
Company's State: NJ  
Company's Country: US  
Company's Zip Code: 07645-5000  
Company's Emerg Ph #: 201-391-0253/201-573-5700  
Company's Info Ph #: 201-573-5700/201-391-0253  
Record No. For Safety Entry: 001  
Tot Safety Entries This Stk#: 001  
Status: SE  
Date MSDS Prepared: 31OCT94  
Safety Data Review Date: 06APR95  
Preparer's Company: MINWAX CO DIV OF EASTMAN KODAK CO  
Preparer's St Or P. O. Box: 15 MERCEDES DRIVE  
Preparer's City: MONTVALE  
Preparer's State: NJ  
Preparer's Zip Code: 07645-5000  
MSDS Serial Number: BWWKR

=====  
Ingredients/Identity Information  
=====

Proprietary: NO  
Ingredient: MEDIUM ALIPHATIC NAPHTHA (AROMATIC 100), PARAFFIN-NAPHTHANES  
MINERAL SPIRITS  
Ingredient Sequence Number: 01  
Percent: 20-26  
NIOSH (RTECS) Number: 1003692SN  
CAS Number: 64742-88-7  
OSHA PEL: 500 PPM  
ACGIH TLV: 100 PPM  
Other Recommended Limit: 100 PPM

-----  
Proprietary: NO

Ingredient: STODDARD SOLVENT (PETROLEUM DISTILLATE), MINERAL SPIRITS

Ingredient Sequence Number: 02

Percent: 29-40

NIOSH (RTECS) Number: WJ8925000

CAS Number: 8052-41-3

OSHA PEL: 500 PPM

ACGIH TLV: 100 PPM

Other Recommended Limit: 525 MG/CUM

-----  
Proprietary: NO

Ingredient: VOLATILE ORGANIC COMPOUNDS: < 540 G/L

Ingredient Sequence Number: 03

NIOSH (RTECS) Number: 9999999VO  
=====

#### Physical/Chemical Characteristics

=====

Appearance And Odor: CLEAR AMBER LIQUID W/HYDROCARBON ODOR

Specific Gravity: 0.871

Solubility In Water: INSOLUBLE  
=====

#### Fire and Explosion Hazard Data

=====

Flash Point: >101F

Flash Point Method: SCC

Extinguishing Media: WATER SPRAY, FOAM, DRY CHEMICAL/CO2.

Special Fire Fighting Proc: DON'T USE A DIRECT STREAM OF WATER. WEAR SCBA  
& PROTECTIVE CLOTHING. USE WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS.

Unusual Fire And Expl Hazrds: COMBUSTIBLE. PRODUCT MAY FLOAT & CAN BE  
IGNITED ON SURFACE OF WATER. CONTAINERS EXPOSED TO INTENSE HEAT MAY  
RUPTURE.  
=====

#### Reactivity Data

=====

Stability: YES

Cond To Avoid (Stability): HEAT, SPARKS, OPEN FLAME & OTHER SOURCES OF  
IGNITION.

Materials To Avoid: STRONG OXIDIZING AGENTS.

Hazardous Decomp Products: HYDROCARBON FUMES, SMOKE, CO.

Hazardous Poly Occur: NO  
=====

#### Health Hazard Data

=====

Route Of Entry - Inhalation: YES

Route Of Entry - Skin: NO

Route Of Entry - Ingestion: YES

Health Haz Acute And Chronic: SKIN: IRRITANT. INGESTION: HARMFUL/FATAL.

Carcinogenicity - NTP: NO

Carcinogenicity - IARC: NO

Carcinogenicity - OSHA: NO

Explanation Carcinogenicity: NONE

Signs/Symptoms Of Overexp: IRRITATION.

Med Cond Aggravated By Exp: PRE-EXISTING LUNG DISORDERS

WASH THOROUGHLY W/SOAP & WATER. EYES: REMOVE CONTACT LENSES, FLUSH W/ PLENTY OF WATER. INGESTION: DON'T INDUCE VOMITING. OBTAIN MEDICAL ATTENTION

IN ALL CASES.

Precautions for Safe Handling and Use

Steps If Matl Released/Spill: SMALLS: ABSORB W/SAND/OTHER SUITABLE ABSORBENT MATERIAL & PLACE IN A CONTAINER FOR DISPOSAL. LARGE: AREA MAY BE SLIPPERY, DIKE AROUND W/ABSORBENT MATERIAL. TRANSFER LIQUIDS & CONTAMINATED

DIKING MATERIAL TO SEPERATE CONTAINERS FOR RECOVERY/DISPOSAL.

Waste Disposal Method: DISPOSE OF IAW/FEDERAL, STATE & LOCAL REGULATIONS.

Precautions-Handling/Storing: DON'T USE/STORE NEAR HEAT, SPARKS, FLAME/ OTHER SOURCES OF IGNITION. CLOSE CONTAINER AFTER EACH USE.

Other Precautions: DON'T TAKE INTERNALLY. AVOID CONTACT W/SKIN/EYES. KEEP OUT OF REACH OF CHILDREN. AVOID INHALATION, USE ONLY W/ADEQUATE VENTILATION.

Control Measures

Respiratory Protection: WEAR NIOSH/MSHA/EQUIVALENT RESPIRATOR/LEAVE AREA.

Ventilation: REQUIRED

Protective Gloves: RUBBER

Eye Protection: SAFETY GLASSES

Transportation Data

Disposal Data

Label Data

Label Required: YES

Label Status: G

Common Name: MO60370 MINWAX FAST DRYING POLYURETHANE CLEAR-ALL FINISHES

Special Hazard Precautions: SKIN: IRRITANT. INGESTION: HARMFUL/FATAL. IRRITATION.

Label Name: MINWAX CO DIV OF EASTMAN KODAK CO

Label Street: 15 MERCEDES DRIVE

Label P.O. Box: 438

Label City: MONTVALE

Label State: NJ

Label Zip Code: 07645-5000

Label Country: US

Label Emergency Number: 201-391-0253/201-573-5700

=====  
URL for this msds <http://hazard.com>. If you wish to change, add to, or delete information in this archive please sent updates to [dan@hazard.com](mailto:dan@hazard.com).