

Chemical Name: Lifetime Adhesive Sealant

Manufacturer: Red Devil

Container size: 10.1oz.

Location: VLA

Disposal: Place empty container in trash.

Material Safety Data Sheet

0856 Series Lifetime Pro Adhesive Sealant – White & Colors

MSDS No. 0097 Rev. 7

Emergency Phone No. (918)825-5744

					(210)0	25-5744	
	SECTION 1 – I	PRODUCT NAME & 1	MANUFACTURER 1	INFORM	ATION		
PRODUCT NAME	Lifetime Pro Adhe	esive Sealant – White & Colors					
MANUFACTURER'S I		918-825-5744					
STREET ADDRESS	4175 Webb Street						
CITY / STATE / ZIP	Pryor, Oklahoma	74361					
SECTIO	ON 2 – COMPOSIT	ION / HAZARDOUS 1	INGREDIENTS	%	TLV	PEL	UNITS
PRODUCT CONSISTS	S OF:						
Calcium Cart	bonate ** (1317-65-3)			< 55	10	15	mg/m3
Acrylic Emu	lsion (mixture)			< 30	NE	NE	
Benzoate Este	er (proprietary)			< 8	NE	NE	
Petroleum Di	stillate (64742-48-9)			< 1	100	100	ppm
Titanium Dio	oxide ** (13463-67-7)			< 1.5	10	10	mg/m3
Ammonium I	Hydroxide (7664-41-7)			< 0.25	25	50	ppm
Non-hazardoı	us ingredients*			< 10	NA	NA	
*Unlisted ingredients are not considered hazardous under the OSHA Hazard Communication Standard (29 CFR 1910.1200). **Inhalation not likely due to products physical state. Calculated VOC: < 1.5%/wt (<25 g/L). CARB Compliance: Yes. Prop 65 Ingredients: Yes (See Section 16)							
		SECTION 3 – HAZAR	DS IDENTIFICATION)N	_		
	3			JIN			
PRIMARY ROUTE(S) OF ENTRY	Skin Contact	Skin Absorption	Eye Contact	∑ Inhala	tion	⊠ Inge	estion
ROUTE(S) OF	Skin Contact		Eye Contact		tion	⊠ Inge	estion
ROUTE(S) OF ENTRY EMERGENCY	Skin Contact Colored paste product. Harm	Skin Absorption	Eye Contact		tion	⊠ Inge	estion
ROUTE(S) OF ENTRY EMERGENCY OVERVIEW EFFECTS OF	Skin Contact Colored paste product. Harm	Skin Absorption Iful if swallowed or absorbed throug	Eye Contact		tion	⊠ Ingo	estion
ROUTE(S) OF ENTRY EMERGENCY OVERVIEW EFFECTS OF OVEREXPOSURE MEDICAL CONDITIONS AGGRAVATED BY	Skin Contact Colored paste product. Harm May cause eye, skin, nose, th	Skin Absorption If ul if swallowed or absorbed through the arroat & respiratory tract irritation.	Eye Contact		tion	⊠ Ingo	estion
ROUTE(S) OF ENTRY EMERGENCY OVERVIEW EFFECTS OF OVEREXPOSURE MEDICAL CONDITIONS AGGRAVATED BY	Skin Contact Colored paste product. Harm May cause eye, skin, nose, th None known.	Skin Absorption If ul if swallowed or absorbed through the arroat & respiratory tract irritation.	Eye Contact th skin. T AID MEASURES	⊠ Inhala			
ROUTE(S) OF ENTRY EMERGENCY OVERVIEW EFFECTS OF OVEREXPOSURE MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE	Skin Contact Colored paste product. Harm May cause eye, skin, nose, th None known.	Skin Absorption Skin Absorption SECTION 4 – FIRS	Eye Contact th skin. T AID MEASURES medical attention if symptoms per	☑ Inhala	wash contan	ninated clothi	
ROUTE(S) OF ENTRY EMERGENCY OVERVIEW EFFECTS OF OVEREXPOSURE MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE SKIN CONTACT	Skin Contact Colored paste product. Harm May cause eye, skin, nose, th None known. Wash w/ soap & Immediately flu	Skin Absorption If ul if swallowed or absorbed through the swallowed or a	Eye Contact The skin. TAID MEASURES medical attention if symptoms per least 15 minutes until irritation s	Inhala rsist. Remove & subsides. Get me	wash contan	ninated clothi	

SECTION 5 – FIRE FIGHTING MEASURES							
FLAMMABLE Yes No							
EXTINGUISHING Carbon Dioxide, Dry Chemical, Foam, Water Fog MEDIA							
FLASHPOINT (°F) & >200F (Closed Cup) METHOD	UPPER EXPLOSIVE LIMIT NE (% BY VOLUME)						
LOWER EXPLOSIVE LIMIT NE (% BY VOLUME)	AUTOIGNITION NE TEMPERTURE (°F)						
UNUSUAL FIRE & EXPLOSION HAZARDS None known.							
SPECIAL Wear self-contained breathing apparatus pressure demand (NIOSH approved or equivalent) & full protective gear. Use water spray to FIREFIGHTING PROCEDURES Wear self-contained breathing apparatus pressure demand (NIOSH approved or equivalent) & full protective gear. Use water spray to cool exposed surfaces.							
SECTION 6 – ACCIDENTAL RELEASE MEASURES							
PROCEDURES Wear proper protective equipment (Section 8). Use absorbent material or scrape up dried material & place in approved container.							
SECTION 7 – HANI	DLING & STORAGE						
HANDLING PROCEDURES & EQUIPMENT Keep out of reach of children & pets. Do not take internally. Do not breathe vapors. Use only w/ adequate ventilation. Wash thoroughly after handling. Avoid contact w/ eyes, skin & clothing. Open windows & doors to ensure cross-ventilation & fresh air during application & curing.							
STORAGE REQUIREMENTS Close container after each use. Store containers away from excessive heat & freezing. Do not store @ temperatures above 120F. Store away from caustics & oxidizers.							
SECTION 8 – EXPOSURE CONTROL / PERSONAL PROTECTION							
RESPIRATORY In case of insufficient ventilation, wear suitable respiratory equipment. A NIOSH-approved air purifying respirator w/ organic vapor cartridge may be necessary under circumstances where concentrations are expected to exceed exposure limits.							
EYEWEAR Goggles or safety glasses w/ side shields.							
CLOTHING / GLOVES Rubber gloves. Other protective equipment not required under normal use.							
HYGENIC PRACTICES Remove & wash contaminated clothing before re-use. Wash hands before breaks & @ end of workday.							
SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES							
1 4510	OOR & Mild acrylic. Smooth paste. PEARANCE						
	APOR DENSITY Heavier than air IR=1)						
EVAPORATION RATE Slower than n-Butyl Acetate BC	DILING RANGE (°F) 210 to 220F						
	OLUBILITY IN Slight, before cure.						
	TWT VOLATILE 15 to 25% NV)						
SECTION 10 – STABILITY AND REACTIVITY							
STABILITY Yes No Stable under normal conditions.							
INCOMPATABILITY Yes No Incompatible w/ strong bas	es & oxidizing agents.						
CONDITIONS TO AVOID Excessive heat & freezing.							
HAZARDOUS POLYMERIZATION/HAZARDOUS DECOMPOSITION PRODUCTS Hazardous polymerization will not occur under normal conditions. Normal decomposition products, ie: COx, NOx.							

ACGIH	Small amount of Silica, crystalline present in Calcium Carbonate & trace residual Formaldehyde present in base emulsion are suspected human carcinogens.		
OSHA	Trace residual Formaldehyde present in base emulsion viewed as a possible cancer hazard.		
IARC	Trace residual Formaldehyde: Human carcinogen.		
NTP	Silica, crystalline, present in small amount in Calcium Carbonate Filler: Known carcinogen. Trace residual Formaldehyde: Anticipated carcinogen		
DATA WITH POSSIBLE RELEVANCE TO HUMANS	Product contains trace amounts of residual Formaldehyde. OSHA & NTP identify Formaldehyde as a potential carcinogen. IARC identifies Formaldehyde as a human carcinogen. Formaldehyde has been shown to cause mutations in a variety of in-vitro test systems, w/ human significance unknown. Rats have shown carcinogenic effects in respiratory system. Risk should be minimal when used w/ adequate ventilation. Maintain adequate ventilation to prevent exposure above OSHA exposure limits.		
	SECTION 12 – ECOLOGICAL INFORMATION		
AQUATIC TOXICITY	Not known or expected under normal use.		

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL

Dispose of material in accordance w/ Federal, State & Local regulations.

EPA WASTE CODE IF DISCARDED (40CFR Sec.261)

None.

SECTION 14 – TRANSPORT INFORMATION

SPECIAL SHIPPING INFORMATION

Shipping information applicable for domestic ground transport only. Different categorization may be necessary if shipped via other modes of transportation &/or to non-domestic destinations. PRODUCT NOT REGULATED BY DOT.

SECTION 15 – REGULATORY INFORMATION						
CERCLA – SARA HAZARD CATEGORY	Immediate health hazard; chronic health hazard.	U.S. STATE REGS	See Section 16.			
SARA 313	None.	TSCA	All ingredients either on TSCA Inventory or exempt.			

SECTION 16 - OTHER INFORMATION / SPECIAL PRECAUTIONS / LEGEND

NJ Right-to-Know: (Top 5 Ingredients): Calcium Carbonate (1317-65-3), Base Acrylic Emulsion (mixture), Benzoate Ester (proprietary), Water (7732-18-5), Propylene Glycol (57-55-6). Pennsylvania Right-to-Know (Non-Haz @ >3%): Water (7732-18-5). Ingredients Known to State of California to cause cancer &/or developmental toxicity &/or reproductive toxicity: Formaldehyde (50-00-0), Silica, crystalline (14808-60-7). HMIS Ratings: Health: 1, Flammability: 1, Reactivity: 0, Personal Protection: B. Titanium Dioxide (13463-67-7) added to Massachusetts Right to Know List, Minnesota Hazardous Substance List, New Jersey Right to Know List, Pennsylvania Right to Know List & Rhode Island Hazardous Substance List. WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. Non-white colors may contain carbon black in color dispersion.

<u>LEGEND</u>: NA – Not Applicable, NE – Not Established, UN – Unavailable, VOC – Volatile Organic Compound, PEL – Permissible Exposure Limit, TLV – Threshold Limit Value, STEL – Short Term Exposure Limit, MSDS – Material Safety Data Sheet, ACGIH – American Conference of Governmental Industrial Hygienists, SARA – Superfund Amendments & Reauthorization Act of 1986, OSHA – Occupational Safety & Health Administration, HMIS – Hazardous Materials Identification System, NTP – National Toxicology Program, CEIL – Ceiling Exposure Limit, CASRN (CAS Number) – Chemical Abstracts Service Registry Number, TSCA – Toxic Substances Control Act

Reviewed By: Larry G. Brandon VP Technology & General Manager February 4, 2010

NAME TITLE DATE

The information contained herein has been developed based upon currently available scientific data. New information may be developed from time to time which may render the conclusions of this report obsolete. Therefore, no warranty is extended as to the applicability of this information to the user's intended purpose or for the consequences of its use or misuse.