

Chemical Name: Super Oil

Manufacturer: Gunk Liquid Wrench

Container size: 4oz.

Location: VLA

<u>Disposal:</u> Place empty container in trash. Give partial or full container to safety officer.

Page 1 of 4 Tuesday, August 30, 2011

MSDS - Material Safety Data Sheet Product Name: LIQUID WRENCH PENETRATING OIL (Liquid)

MSDS No.: L104

I. Basic Information:

Manufacturer: RADIATOR SPECIALTY COMPANY

Address: 600 RADIATOR ROAD
City, ST Zip: INDIAN TRAIL, NC 28079

Country:

Contact: Robert Geer

Information Telephone Number: 704-684--181 1
Emergency Contact: RMPDC (877-740-5015)
Emergency Telephone Number: 303-623-5716

Emergency Restrictions:

Product Name: LIQUID WRENCH PENETRATING OIL (Liquid)

MSDS No.: L104

Issue Date: 08/30/2011 **Supersedes Date:** 09/13/2010

II. Hazards Identification:

EMERGENCY OVERVIEW

Caution: Eye and skin irritant. Rags, steel wool or waste contaminated with this product may sponetaneously catch fire if improperly discarded.

OSHA Regulatory Status

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Potential Health Effects

Route(s) of Entry:

Absorption, Inhalation, and Ingestion.

Health Hazards (Acute and Chronic):

See Signs and Symptoms below.

Signs and Symptoms:

Eye Contact: Irritant. Prolonged contact can cause conjunctivitis.

Skin Contact: Prolonged or repeated skin contact may cause drying, cracking or irritation.

Inhalation: Will not produce vapors unless heated to temperature of 300°F.

Ingestion: Small amounts swallowed are not likely to cause injury. Larger amounts may cause nausea and vomiting.

Medical Conditions Generally Aggravated by Exposure:

Unknown

Other Health Warnings:

Unknown

Potential Environmental Effects

Not Available

III. Composition/Information on Ingredients:

Chemical Name	CAS No.	% Range	Trade Secret
Corrosion Inhibitor	Proprietary	1.0 - 5.0	
Hydrocarbon Fluid	64742-47-8	7.0 - 13.0	
Methyl soyate	67784-80-9	60.0 - 100.0	
PTFE/boron nitride colloid	Proprietary	0.1 - 1.0	
Tripropylene Glycol Monomethyl Ether	25498-49-1	3.0 - 7.0	

IV. First Aid Measures:

Emergency and First Aid Procedures:

Page 2 of 4 Tuesday, August 30, 2011

MSDS - Material Safety Data Sheet Product Name: LIQUID WRENCH PENETRATING OIL (Liquid)

MSDS No.: L104

Eye Contact: Flush eyes with clean water for 15 minutes while lifting eyelids. Get prompt medical attention.

Skin Contact: Wash with soap and water thoroughly. If adverse effects persist, get prompt medical attention. Launder contaminated clothing

before reuse.

Inhalation: Remove to fresh air. If breathing becomes difficult give oxygen and get prompt medical attention. If breathing stops, give artificial

respiration and get prompt medical attention.

Ingestion: DO NOT INDUCE VOMITING! Call Poison Control Center, physician, or hospital emergency room immediately.

Note to Physicians:

N/E

V. Fire Fighting Measures:

Suitable Extinguishing Media:

Water Fog, Foam, Carbon Dioxide, Dry Chemical

Unsuitable Extinguishing Media:

Do not use forced water stream as this could cause the fire to spread.

Products of Combustion:

Normal products of combustion, smoke, carbon dioxide, carbon monoxide, and sulfur trioxides.

Protection of Firefighters:

Wear self-contained positive pressure breathing apparatus and protective clothes. Use shield to protect from rupturing and venting containers. At elevated temperatures containers may vent, rupture or burst, even violently

VI. Accidental Release Measures:

Personal Precautions:

Eliminate all ignition sources. Persons not wearing protective equipment should be excluded from area of spill until clean up has been completed.

Environmental Precautions:

Prevent run-off to sewers, streams, or other bodies of water. If run-off occurs, notify proper authorities as required that a spill has occurred. Run off to sewer may create fire or explosion hazard.

Methods for Containment:

Dike or contain spill and absorb with inert materials (sand, sawdust, absorbent sweeping compounds, rags, etc).

Methods for Cleanup:

Using a non-metalic scoop, place contaminated material into an approved chemical waste container. Where possible, vacuum spilled liquid to recover material.

Other Information:

All equipment used with handling the concentrate must be grounded. If run-off occurs, notify proper authorities as required that a spill has occurred.

VII. Handling and Storage:

Handling Precautions:

Handling: Use with adequate ventilation and proper protective equipment. Contact lenses may cause further damage in case of splash into eye. KEEP AWAY FROM CHILDREN AND ANIMALS!

Storage Precautions:

Store in a cool, dry area away from oxidizers.

VIII. Exposure Controls/Personal Protection:

Chemical Name	OSHA PEL	ACGIH TLV	Other Limits
Methyl soyate	N/E	N/E	Not Available
Tripropylene Glycol Monomethyl Ether	N/E	N/E	Not Available
Hydrocarbon Fluid	5 mg/m3	5 mg/m3	Not Available
PTFE/boron nitride colloid	N/E	N/E	Not Available
Corrosion Inhibitor	N/E	N/E	Not Available

Page 3 of 4 Tuesday, August 30, 2011

MSDS - Material Safety Data Sheet Product Name: LIQUID WRENCH PENETRATING OIL (Liquid)

MSDS No.: L104
Engineering Controls:

Use with adequate ventilation. If TLV is exceeded, wear NIOSH approved respirator.

Personal Protective Equipment:

For prolonged exposure wear protective safety glasses, gloves, and apron.

IX. Physical and Chemical Properties:

Boiling Point:320 FMelting Point:N/DBoiling Range:N/DFreezing Point:N/D

Solubility In Water: Insoluble Evaporation Rate (Butyl Acetate = 1): N/A

Flash Point: > 200°F Flash Point Method: TCC

Odor Threshold: N/D Appearance and Odor: opaque yellow liquid with fragrance

 Vapor Density (AIR = 1): N/D
 Vapor Pressure (mm Hg.): N/D

 pH Range: N/A
 Partition Coefficient: N/D

 Decomposition Temp: N/D
 Auto-Ignition Temp: N/D

 Lower Explosive Limit: N/E
 Upper Explosive Limit: N/E

Specific Gravity (H20 = 1): 0.89
Other Information: VOC Content: 0.%

X. Stability and Reactivity:

Stability:

Product is stable

Conditions to Avoid:

See Incompatible Materials below

Incompatible Materials:

Avoid contact with strong oxidizing agents, acetaldehyde, acids, bases and chlorine.

Hazardous Decomposition Products:

Normal products of combustion, smoke, carbon dioxide, carbon monoxide, and sulfur trioxides.

Possibility of Hazardous Reactions:

Will not occur

XI. Toxicological Information:

Not Established

XII. Ecological Information:

Not Established

XIII. Disposal Considerations:

DISPOSAL: This container may be recycled in a recycling centers when empty. Before offering for recycling, empty the can or bottle by using the product according to the label. If recycling is not available, wrap the container and discard in the trash. Dispose of unused product in accordance with all local, state government and federal laws and regulations

XIV. Transport Information:

Shipping Name: Not Available

MSDS - Material Safety Data Sheet Product Name: LIQUID WRENCH PENETRATING OIL (Liquid)

MSDS No.: L104

DOT Hazard Class: Not Available DOT Subsidiary Hazard Class: Not Available

UN/NA#: Not Available **Packing Group:** Not Available

Transportation Information:

DOT Shipping Name: Not DOT regulated.

DOT Hazard Class: None

The above DOT description is provided to assist in the proper shipping classification of this product by ground and may not be suitable for all

shipping purposes.

For international shipping: ICAO, AND IMDG

Not Regulated

XV. Regulatory Information:

SARA 313 Reportable Chemicals.

USA TSCA: All components of this material are listed on the US TSCA Inventory.

State RTK Chemicals:

Glycol Ether TPM CAS# 25498-49-1

XVI. Other Information:					
Chemical State: Chemical Type:	X Liquid Pure	Gas Mixture		NFPA Fire 1 Health Reastivity	
Hazard Category: X Acute	Chronic Pressure	X Fire Reactive	•	1 0 Special	
Additional Manufacturer Warnings:					
Do not used in confined area without proper ventilation. Contact lenses may cause further damage in case of splash into eye. KEEP AWAY FROM CHILDREN AND ANIMALS!			1 Health 1 Flammability		

Physical Hazard

Pers. Protection

С

N/E: Not Established N/D: Not Determined N/A: Not Applicable N/AV: Not Available

Additional Product Information:

While Radiator Specialty Company believes this data is accurate as of the revision date, we make no warranty with respect to the data and we expressly disclaim all liability for reliance thereon. The data is offered solely for information, investigation, and verification. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this MSDS. The user is responsible for full compliance.