

Chemical Name: High Temperature Gasket Eliminator 510 Sealant

Manufacturer: Loctite Corporation

Container Size: 1.69 oz.

Location: VLA

**Disposal:** Place empty container in trash. Give partial or full container to safety officer.

# **Material Safety Data Sheet**





## **1. PRODUCT AND COMPANY IDENTIFICATION**

Product name: Product type:

me: 50ML GASKET ELIMINATOR 510 pe: Anaerobic Sealant

**Company address:** Henkel Corporation One Henkel Way Rocky Hill, Connecticut 06067

Revision Number: 005.1

IDH number:135474Item number:51031Region:United StatesContact information:Elephone: 860.571.5100MEDICAL EMERGENCY Phone: Poison Control Center1-877-671-4608 (toll free) or 1-303-592-1711TRANSPORT EMERGENCY Phone: CHEMTREC1-800-424-9300 (toll free) or 1-703-527-3887Internet: www.henkelna.com

# 2. HAZARDS IDENTIFICATION

		EMERGENCY OVERVIEW HMIS:	
Physical state:	Gel	HEALTH:	*3
Color:	Pink	FLAMMABILITY:	1
Odor:	Mild	PHYSICAL HAZARD:	1
		Personal Protection:	See MSDS Section 8
WARNING	G:	HARMFUL IF INHALED.	
		MAY CAUSE RESPIRATORY TRACT IRRITATION.	
		MAY CAUSE ALLERGIC SKIN REACTION.	
		CAUSES EYE IRRITATION.	
Relevant routes of exponential Health Effe		Lungs, Eyes, Skin	
Inhalatio	n:	May be toxic if inhaled. May cause respiratory tract irritation.	
Skin con		May cause allergic skin reaction.	
Eye contact: Ingestion:		Contact with eyes will cause irritation. Not expected to be harmful by ingestion.	
ingestion		Not expected to be naminal by ingestion.	
Existing conditions a exposure:	aggravated by	<ul> <li>Eye, skin, and respiratory disorders.</li> </ul>	
		This material is considered hazardous by the OSHA Hazard Con 1910.1200).	nmunication Standard (29 CFF

See Section 11 for additional toxicological information.

#### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
Polyglycol dimethacrylate	25852-47-5	30 - 60
Bisphenol A fumarate resin	39382-25-7	10 - 30
Adipic acid polymer with neopentylglycol, 1,4-butanediol and isononanol	208945-12-4	10 - 30
1,1'-(methylenedi-p-phenylene)bismaleimide	13676-54-5	5 - 10
Silica, amorphous, fumed, crystal-free	112945-52-5	1 - 5
Saccharin	81-07-2	1 - 5
Cumene hydroperoxide	80-15-9	1 - 5
1-Acetyl-2-phenylhydrazine	114-83-0	0.1 - 1

Inhalation:	If symptoms develop and persist, get medical attention. Move to fresh air.
Skin contact:	Wash with soap and water. If symptoms develop and persist, get medical attention. Remove contaminated clothing and footwear. Wash clothing befo reuse.
Eye contact:	Get medical attention. Flush with copious amounts of water, preferably, lukewarm water for at least 15 minutes, holding eyelids open all the time.
Ingestion:	Get medical attention. Do not induce vomiting. Keep individual calm.
5. FIF	RE FIGHTING MEASURES
Flash point:	> 93.3 °C (> 199.94 °F) None
Autoignition temperature:	Not available
Flammable/Explosive limits - lower:	Not available
Flammable/Explosive limits - upper:	Not available
Extinguishing media:	Foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such a turn-out gear.
Unusual fire or explosion hazards:	None
Hazardous combustion products:	Oxides of sulfur. Oxides of nitrogen. Oxides of carbon. Irritating organic vapours.

## 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.		
Environmental precautions:	Do not allow product to enter sewer or waterways.	
Clean-up methods:	Store in a partly filled, closed container until disposal. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).	
7	HANDLING AND STORAGE	

#### 7. HANDLING AND STORAGE

Handling:	Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Use only with adequate ventilation.
Storage:	For safe storage, store between 0 °C (32°F) and 38 °C (100.4 °F) Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Polyglycol dimethacrylate	None	None	None	None
Bisphenol A fumarate resin	None	None	None	None
Adipic acid polymer with neopentylglycol, 1,4- butanediol and isononanol	None	None	None	None
1,1'-(methylenedi-p-phenylene)bismaleimide	None	None	None	None
Silica, amorphous, fumed, crystal-free	10 mg/m3 TWA Inhalable dust. 3 mg/m3 TWA Respirable fraction.	20 MPPCF TWA 0.8 mg/m3 TWA	None	None
Saccharin	None	None	None	None
Cumene hydroperoxide	None	None	1 ppm (6 mg/m3) TWA (SKIN)	None
1-Acetyl-2-phenylhydrazine	None	None	None	None

Engineering controls:

No specific ventilation requirements noted, but forced ventilation may still be required if concentrations exceed occupational exposure limits.

**Respiratory protection:** 

Eye/face protection:

Skin protection:

Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

Safety goggles or safety glasses with side shields.

Natural rubber gloves. Use impermeable gloves and protective clothing as necessary to prevent skin contact. Butyl rubber gloves. Neoprene gloves.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

- Physical state: Color: Odor: Odor threshold: pH: Vapor pressure: Boiling point/range: Melting point/ range: Specific gravity: Vapor density: Flash point: Flammable/Explosive limits - lower: Flammable/Explosive limits - upper: Autoignition temperature: Evaporation rate: Solubility in water: Partition coefficient (n-octanol/water): **VOC content:**
- Gel Pink Mild Not available Not applicable < 5 mm hg (80 °F (26.7 °C)) > 300 °F (> 148.9 °C) None Not available 1.1784 Not available > 93.3 °C (> 199.94 °F) None Not available Not available Not available Not available Slight Not available < 4 % (calculated)

#### **10. STABILITY AND REACTIVITY**

Stability:	Stable
Hazardous reactions:	Will not occur.
Hazardous decomposition products:	Irritating organic vapours. Oxides of sulfur. Oxides of carbon. Oxides of nitrogen.
Incompatible materials:	Strong oxidizing agents.
Conditions to avoid:	See "Handling and Storage" (Section 7) and "Incompatibility" (Section 10).

# **11. TOXICOLOGICAL INFORMATION**

Acute oral product toxicity:

LD50 (rat) > 10,000 mg/kg

IDH number: 135474

Product name: 50ML GASKET ELIMINATOR 510

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)	
Polyglycol dimethacrylate	No	No	No	
Bisphenol A fumarate resin	No	No	No	
Adipic acid polymer with neopentylglycol, 1,4-butanediol and isononanol	No	No	No	
1,1'-(methylenedi-p- phenylene)bismaleimide	No	No	No	
Silica, amorphous, fumed, crystal-free	No	No	No	
Saccharin	No	No	No	
Cumene hydroperoxide	No	No	No	
1-Acetyl-2-phenylhydrazine	No	No	No	
Hazardous components		Health Effects/Targe	t Organs	
Polyglycol dimethacrylate		Irritant, Allergen		
Bisphenol A fumarate resin		No Target Organs		
Adipic acid polymer with neopentylglycol, 1,4-	butanediol	No Data		

and isononanol	No Data
1,1'-(methylenedi-p-phenylene)bismaleimide	No Target Organs
Silica, amorphous, fumed, crystal-free	Nuisance dust
Saccharin	No Target Organs
Cumene hydroperoxide	Allergen, Central nervous system, Corrosive, Irritant, Mutagen
1-Acetyl-2-phenylhydrazine	Allergen, Blood, Kidney, Mutagen, Some evidence of carcinogenicity

# **12. ECOLOGICAL INFORMATION**

Ecological information:

Not available

# **13. DISPOSAL CONSIDERATIONS**

Information provided is for unused product only.

Recommended method of disposal:

Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number:

Not a RCRA hazardous waste.

## **14. TRANSPORT INFORMATION**

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None
nternational Air Transportation (ICAO/I	ΑΤΑ)
Proper shipping name:	Environmentally hazardous substance, liquid, n.o.s. (Diphenylmethane Bismaleimide)
Hazard class or division:	9
Identification number:	UN 3082
Packing group:	III
Water Transportation (IMO/IMDG)	
Proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Diphenylmethane Bismaleimide)
Hazard class or division:	9
Identification number:	UN 3082
Packing group:	
Marine pollutant:	Diphenylmethane Bismaleimide

### 15. REGULATORY INFORMATION

**United States Regulatory Information** TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory. TSCA 12(b) Export Notification: None above reporting de minimus CERCLA/SARA Section 302 EHS: None above reporting de minimus CERCLA/SARA Section 311/312: Delayed Health, Immediate Health CERCLA/SARA 313: This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Cumene hydroperoxide (CAS# 80-15-9). California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm. **Canada Regulatory Information CEPA DSL/NDSL Status:** All components are listed on or are exempt from listing on the Canadian Domestic Substances List. WHMIS hazard class: D.1.A, D.2.B **16. OTHER INFORMATION** 

This material safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format. 2

Prepared by: Kyra Kozak Woods, Manager, Regulatory Affairs

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.