



Chemical Name: Foil Tape


Manufacturer: Polyken

Container size: NA

Location: VLA

Disposal: Place empty container in trash.

Premium Foil Tape



- Backing:** 2.0 mil Aluminum Foil
- Adhesive:** Synthetic Rubber
- Liner:** Unbleached Natural Kraft Paper
- Colors:** Aluminum
- Specifications:** UL 723 Listed
- Standard Sizes:** 48mm x 46M, 72mm x 46M

Applications

- Taping joints and seams in duct work for A/C, heating, and ventilation systems
- General purpose industrial and automotive uses
- Insulation seaming and patching

Features

- 2.0 mil Aluminum Foil Backing
- Synthetic Rubber Adhesive
- UL 723 Listed
- Low VOC Content

Benefits

- Conformable to fit corners and joints
- UV, moisture and mold resistant
- Non-solvent for less odor and low VOC content
- Extreme high tack, aggressive bond to surfaces
- Good all-weather performance
- Meets flammability requirements for use in construction and marine applications
- Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

Physical Properties

	Standard UOM	Metric UOM	Test Method
Total Thickness	3.7 mils	93.98 mic	ASTM D-1000
Foil Thickness	1.8 mils	45.72 mic	ASTM D-1000
Adhesion to Steel	100 oz/in	10.95 N/cm	PSTC-101
Tensile Strength	14 lb/in	24.52 N/cm	ASTM D-1000
Operating Temperature	40 to 200 °F	4 to 93 °C	
Smoke Developed	10		
Flame Spread	10		
VOC Content	<1 g/L		

Recommended Storage Conditions: 40-60% Humidity, 60°F-80°F
 Standard Shelf Life (at 25C): 36 months from date of manufacture.

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry Plastics' knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.