



**Chemical Name:** SAE 75W-140 Gear Oil

**Manufacturer:** Valvoline

**Container size:** 1 qt.

**Location:** VLA

**Disposal:** Place empty container in trash. Give partial or full container to safety officer.

## SAFETY DATA SHEET

Revision Date: 12/13/2011

Print Date: 5/23/2012

MSDS Number: R0388288

Version: 2.0

Synpower™ 75W140 GEAR OIL  
3634

### 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Ashland	Regulatory Information Number	1-800-325-3751
P.O. Box 2219	Telephone	614-790-3333
Columbus, OH 43216	Emergency telephone number	1-800-ASHLAND (1-800-274-5263)

Product name                      Synpower™ 75W140 GEAR OIL

Product code                      3634

### 2. HAZARDS IDENTIFICATION

#### Emergency Overview

Appearance: liquid, amber

WARNING!    MAY CAUSE ALLERGIC SKIN REACTION. PROLONGED OR REPEATED CONTACT MAY DRY THE SKIN AND CAUSE IRRITATION AND BURNS.

#### Potential Health Effects

##### **Exposure routes**

Inhalation, Skin absorption, Skin contact, Eye Contact, Ingestion

##### **Eye contact**

Unlikely to cause eye irritation or injury.

##### **Skin contact**

May cause mild skin irritation. Symptoms may include redness and burning of skin. May cause allergic skin reaction. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, and drying and cracking of skin, skin burns, and other skin damage.

##### **Ingestion**

## SAFETY DATA SHEET

Revision Date: 12/13/2011

Print Date: 5/23/2012

MSDS Number: R0388288

Version: 2.0

Synpower™ 75W140 GEAR OIL  
3634

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.

### Inhalation

It is possible to breathe this material under certain conditions of handling and use (for example, during heating, spraying, or stirring). Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.).

### Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: Skin, lung (for example, asthma-like conditions)

### Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways)

### Target Organs

Chronic feeding studies with white oils (greater than 0.5% in the diet) have resulted in increased organ weights (liver, kidney, spleen), and in microscopic areas of oil accumulation in the liver and the lymph nodes of the gut in experimental animals. These changes have occasionally been associated with cell damage. In humans, cell damage resulting from accumulation of these oil droplets has only occurred following prolonged ingestion of mineral oil. These effects are not expected to occur as a result of occupational exposure to white oils.

### Carcinogenicity

This material is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA). White mineral oil was not carcinogenic in laboratory animals by any route of exposure other than by injection into the abdomen. Results of abdominal injection are not relevant to possible human exposure to this material.

### Reproductive hazard

There are no data available for assessing risk to the fetus from maternal exposure to this material.

## SAFETY DATA SHEET

Revision Date: 12/13/2011

Print Date: 5/23/2012

MSDS Number: R0388288

Version: 2.0

Synpower™ 75W140 GEAR OIL  
3634

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components	CAS-No. / Trade Secret No.	Concentration
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	>=30-<40%
WHITE MINERAL OIL	8042-47-5	>=1.5-<5%
ALKYLAMINE SALT OF ALKYL PHOSPHORIC ACID		>=1.5-<5%
Phosphoric acid esters, amine salt	91745-46-9	>=1.5-<5%

### 4. FIRST AID MEASURES

#### Eyes

If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.

#### Skin

Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

#### Ingestion

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

#### Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

#### Notes to physician

**Hazards:** Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle

## SAFETY DATA SHEET

Revision Date: 12/13/2011

Print Date: 5/23/2012

MSDS Number: R0388288

Version: 2.0

Synpower™ 75W140 GEAR OIL  
3634

and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.

**Treatment:** No information available.

### 5. FIREFIGHTING MEASURES

#### Suitable extinguishing media

Dry chemical, Carbon dioxide (CO<sub>2</sub>), Water spray

#### Hazardous combustion products

carbon dioxide and carbon monoxide, Hydrocarbons, Hydrogen chloride gas, nitrogen oxides (NO<sub>x</sub>), Oxides of phosphorus

#### Precautions for fire-fighting

Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA). DO NOT direct a solid stream of water or foam into hot, burning pools of liquid since this may cause frothing and increase fire intensity. Frothing can be violent and possibly endanger any firefighter standing too close to the burning liquid. Use water spray to cool fire exposed containers and structures until fire is out if it can be done with minimal risk. Avoid spreading burning material with water used for cooling purposes.

#### NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

### 6. ACCIDENTAL RELEASE MEASURES

#### Personal precautions

For personal protection see section 8. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

#### Environmental precautions

Prevent spreading over a wide area (e.g. by containment or oil barriers). Do not let product enter drains. Do not flush into surface water or sanitary sewer system.

#### Methods for cleaning up

## SAFETY DATA SHEET

Revision Date: 12/13/2011

Print Date: 5/23/2012

MSDS Number: R0388288

Version: 2.0

Synpower™ 75W140 GEAR OIL  
3634

Keep in suitable, closed containers for disposal. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

### Other information

Comply with all applicable federal, state, and local regulations.

## 7. HANDLING AND STORAGE

### Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed.

### Storage

Store in a cool, dry, ventilated area.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Exposure Guidelines

HYDROTREATED LIGHT PARAFFINIC DISTILLATE		64742-55-8	
NIOSH	Recommended exposure limit (REL):	5 mg/m3	Mist.
NIOSH	Short term exposure limit	10 mg/m3	Mist.
OSHA Z1	Permissible exposure limit	5 mg/m3	Mist.
ACGIH	time weighted average	5 mg/m3	Inhalable fraction.
WHITE MINERAL OIL		8042-47-5	
NIOSH	Recommended exposure limit (REL):	5 mg/m3	Mist.
NIOSH	Short term exposure limit	10 mg/m3	Mist.
OSHA Z1	Permissible exposure limit	5 mg/m3	Mist.
ACGIH	time weighted average	5 mg/m3	Inhalable fraction.

### General advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

## SAFETY DATA SHEET

Revision Date: 12/13/2011

Print Date: 5/23/2012

MSDS Number: R0388288

Version: 2.0

Synpower™ 75W140 GEAR OIL  
3634

### Exposure controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

### Eye protection

Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

### Skin and body protection

Wear normal work clothing including long pants, long-sleeved shirts and foot covering to prevent direct contact of the product with the skin. Launder clothing before reuse. If skin irritation develops, contact your facility health and safety professional or your local safety equipment supplier to determine the proper personal protective equipment for your use.

Wear resistant gloves (consult your safety equipment supplier).

Discard gloves that show tears, pinholes, or signs of wear.

### Respiratory protection

A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state</b>	liquid
<b>Colour</b>	amber
<b>Odour</b>	mild
<b>Boiling point/boiling range</b>	626 °F / 330 °C @ 1,013.33 hPa Calculated Phase Transition Liquid/Gas
<b>Flash point</b>	> 390 °F / > 199 °C Cleveland open cup
<b>Evaporation rate</b>	(<)1 Ethyl Ether

## SAFETY DATA SHEET

Revision Date: 12/13/2011

Print Date: 5/23/2012

MSDS Number: R0388288

Version: 2.0

Synpower™ 75W140 GEAR OIL  
3634

<b>Lower explosion limit/Upper explosion limit</b>	1 %(V) / 6 %(V)
<b>Vapour pressure</b>	1.333 hPa @ 68 °F / 20 °C Calculated Vapor Pressure
<b>Relative vapour density</b>	(>)1 AIR=1
<b>Density</b>	0.874 g/cm <sup>3</sup> @ 60.01 °F / 15.56 °C
	7.29 lb/gal
<b>Viscosity, kinematic</b>	25.3 mm <sup>2</sup> /s

## 10. STABILITY AND REACTIVITY

### Stability

Stable.

### Conditions to avoid

excessive heat

### Incompatible products

Strong acids, Strong oxidizing agents

### Hazardous decomposition products

carbon dioxide and carbon monoxide, Hydrocarbons, Hydrogen chloride gas, nitrogen oxides (NO<sub>x</sub>), Oxides of phosphorus

### Hazardous reactions

Product will not undergo hazardous polymerization.

## 11. TOXICOLOGICAL INFORMATION

### Acute oral toxicity

Acute oral toxicity - Product : no data available

Acute oral toxicity - Components

## SAFETY DATA SHEET

Revision Date: 12/13/2011

Print Date: 5/23/2012

MSDS Number: R0388288

Version: 2.0

Synpower™ 75W140 GEAR OIL  
3634

WHITE MINERAL OIL	: LD 50: 50,000 mg/kg Species: Rat
Phosphoric acid esters, amine salt	: LD 50: 2,000 mg/kg Species: Rat

### Acute inhalation toxicity

Acute inhalation toxicity - Product	: no data available
--	---------------------

### Acute dermal toxicity

Acute dermal toxicity - Product	: no data available
------------------------------------	---------------------

### Acute dermal toxicity - Components

WHITE MINERAL OIL	: LD 50: > 2,000 mg/kg Species: Rabbit
-------------------	--

### Acute toxicity (other routes of administration)

Acute toxicity (other routes of administration)	: no data available
--	---------------------

## 12. ECOLOGICAL INFORMATION

### Biodegradability

Biodegradability - Product	: no data available
----------------------------	---------------------

### Bioaccumulation

Bioaccumulation - Product	: no data available
---------------------------	---------------------

### Ecotoxicity effects

#### Toxicity to fish

Toxicity to fish - Product	: no data available
----------------------------	---------------------

### Toxicity to daphnia and other aquatic invertebrates.

Toxicity to daphnia and other aquatic invertebrates.	: no data available
---	---------------------

## SAFETY DATA SHEET

Revision Date: 12/13/2011

Print Date: 5/23/2012

MSDS Number: R0388288

Version: 2.0

Synpower™ 75W140 GEAR OIL  
3634

- Product

### Toxicity to algae

Toxicity to algae - Product : no data available

### Toxicity to bacteria

Toxicity to bacteria - Product : no data available

## 13. DISPOSAL CONSIDERATIONS

### Waste disposal methods

Dispose of in accordance with all applicable local, state and federal regulations.

## 14. TRANSPORT INFORMATION

### REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.
-----------	----------------------	---------------	--------------------	---------------	------------------------------

### U.S. DOT - ROAD

Not dangerous goods

### U.S. DOT - RAIL

Not dangerous goods

### U.S. DOT - INLAND WATERWAYS

Not dangerous goods

### TRANSPORT CANADA - ROAD

## SAFETY DATA SHEET

Revision Date: 12/13/2011

Print Date: 5/23/2012

MSDS Number: R0388288

Version: 2.0

Synpower™ 75W140 GEAR OIL  
3634

Not dangerous goods
---------------------

### TRANSPORT CANADA - RAIL

Not dangerous goods
---------------------

### TRANSPORT CANADA - INLAND WATERWAYS

Not dangerous goods
---------------------

### INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods
---------------------

### INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods
---------------------

### INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods
---------------------

### MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES

Not dangerous goods
---------------------

\*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

## 15. REGULATORY INFORMATION

### California Prop. 65

Proposition 65 warnings are not required for this product based on the results of a risk assessment.	
--	--

### SARA Hazard Classification

### SARA 311/312 Classification

Acute Health Hazard
---------------------

## SAFETY DATA SHEET

Revision Date: 12/13/2011

Print Date: 5/23/2012

MSDS Number: R0388288

Version: 2.0

Synpower™ 75W140 GEAR OIL  
3634

### SARA 313 Component(s)

SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

### New Jersey RTK Label Information

HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8
POLYMER	68037-01-4
DI-TERT-BUTYL POLYSULFIDE	68937-96-2
WHITE MINERAL OIL	8042-47-5
CONTENTS PARTIALLY UNKNOWN	

### Pennsylvania RTK Label Information

HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8
POLYMER	68037-01-4
DI-TERT-BUTYL POLYSULFIDE	68937-96-2
WHITE MINERAL OIL	8042-47-5

### Notification status

US. Toxic Substances Control Act	y (positive listing)
Australia. Industrial Chemical (Notification and Assessment) Act	y (positive listing)
Canada. Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL). (Can. Gaz. Part II, Vol. 133)	y (positive listing)
Japan. Kashin-Hou Law List	n (Negative listing)
Korea. Toxic Chemical Control Law (TCCL) List	y (positive listing)
Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control Act	y (positive listing)
China. Inventory of Existing Chemical Substances	y (positive listing)

	HMIS	NFPA
Health	2	1
Flammability	1	1
Physical hazards	0	
Instability		0

## SAFETY DATA SHEET

Revision Date: 12/13/2011

Print Date: 5/23/2012

MSDS Number: R0388288

Version: 2.0

Synpower™ 75W140 GEAR OIL  
3634

	HMIS	NFPA
Specific Hazard	--	--

### 16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).