



**Chemical Name:** Finish 1 FC710

**Manufacturer:** Acme

**Container size:** 1 gallon

**Location:** VLA

**Disposal:** Place empty container in trash.

# MATERIAL SAFETY DATA SHEET

FC710  
04 00

DATE OF PREPARATION  
Sep 9, 2008

**SECTION 1 — PRODUCT AND COMPANY IDENTIFICATION**

**PRODUCT NUMBER**

FC710

**PRODUCT NAME**

FINISH 1™ Ultimate Spot/Panel Clearcoat (Part A),

**MANUFACTURER'S NAME**

ACME AUTOMOTIVE FINISHES  
101 Prospect Avenue N.W.  
Cleveland, OH 44115

**Telephone Numbers and Websites**

<b>Regulatory Information</b>	(216) 566-2902
<b>Medical Emergency</b>	(216) 566-2917
<b>Transportation Emergency*</b>	(800) 424-9300

*\*for Chemical Emergency ONLY (spill, leak, fire, exposure, or accident)*

**SECTION 2 — COMPOSITION/INFORMATION ON INGREDIENTS**

% by Weight	CAS Number	Ingredient	Units	Vapor Pressure
5	67-64-1	<b>Acetone</b>		
		ACGIH TLV	500 PPM	180 mm
		ACGIH TLV	750 PPM STEL	
		OSHA PEL	1000 PPM	
8	78-93-3	<b>Methyl Ethyl Ketone</b>		
		ACGIH TLV	200 PPM	70 mm
		ACGIH TLV	300 PPM STEL	
		OSHA PEL	200 PPM	
		OSHA PEL	300 PPM STEL	
14	590-01-2	<b>n-Butyl Propionate</b>		
		ACGIH TLV	Not Available	3.44 mm
		OSHA PEL	Not Available	
2	763-69-9	<b>Ethyl 3-Ethoxypropionate</b>		
		ACGIH TLV	Not Available	1.11 mm
		OSHA PEL	Not Available	
27	123-86-4	<b>n-Butyl Acetate</b>		
		ACGIH TLV	150 PPM	10 mm
		ACGIH TLV	200 PPM STEL	
		OSHA PEL	150 PPM	
		OSHA PEL	200 PPM STEL	

**SECTION 3 — HAZARDS IDENTIFICATION**

**ROUTES OF EXPOSURE**

INHALATION of vapor or spray mist.  
EYE or SKIN contact with the product, vapor or spray mist.

**EFFECTS OF OVEREXPOSURE**

**EYES:** Irritation.  
**SKIN:** Prolonged or repeated exposure may cause irritation.  
**INHALATION:** Irritation of the upper respiratory system.

**HMIS Codes**

<b>Health</b>	2
<b>Flammability</b>	3
<b>Reactivity</b>	0

May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death.  
Prolonged overexposure to solvent ingredients in Section 2 may cause adverse effects to the blood forming and reproductive systems.

**SIGNS AND SYMPTOMS OF OVEREXPOSURE**

Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists.  
Redness and itching or burning sensation may indicate eye or excessive skin exposure.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE**

May cause allergic respiratory and/or skin reaction in susceptible persons or sensitization. This effect may be delayed several hours after exposure.

Persons sensitive to isocyanates will experience increased allergic reaction on repeated exposure.

#### CANCER INFORMATION

For complete discussion of toxicology data refer to Section 11.

### SECTION 4 — FIRST AID MEASURES

**EYES:** Flush eyes with large amounts of water for 15 minutes. Get medical attention.

**SKIN:** Wash affected area thoroughly with soap and water.

Remove contaminated clothing and launder before re-use.

**INHALATION:** If any breathing problems occur during use, **LEAVE THE AREA** and get fresh air. If problems remain or occur later, **IMMEDIATELY** get medical attention.

**INGESTION:** Do not induce vomiting. Get medical attention immediately.

### SECTION 5 — FIRE FIGHTING MEASURES

#### FLASH POINT

34° F PMCC

#### LEL

1.0

#### UEL

12.8

#### FLAMMABILITY CLASSIFICATION

RED LABEL -- Flammable, Flash below 100° F (38 °C)

#### EXTINGUISHING MEDIA

Carbon Dioxide, Dry Chemical, Foam

#### UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers may explode when exposed to extreme heat.

Application to hot surfaces requires special precautions.

During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

#### SPECIAL FIRE FIGHTING PROCEDURES

Full protective equipment including self-contained breathing apparatus should be used.

Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

### SECTION 6 — ACCIDENTAL RELEASE MEASURES

#### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

- Remove all sources of ignition. Ventilate the area.
- Remove with inert absorbent.

### SECTION 7 — HANDLING AND STORAGE

#### STORAGE CATEGORY

DOL Storage Class IB

#### PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Contents are **FLAMMABLE**. Keep away from heat, sparks, and open flame.

During use and until all vapors are gone: Keep area ventilated - Do not smoke - Extinguish all flames, pilot lights, and heaters - Turn off stoves, electric tools and appliances, and any other sources of ignition.

Consult NFPA Code. Use approved Bonding and Grounding procedures.

Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally.

Keep out of the reach of children.

### SECTION 8 — EXPOSURE CONTROLS/PERSONAL PROTECTION

#### PRECAUTIONS TO BE TAKEN IN USE

**NO PERSON SHOULD USE THIS PRODUCT, OR BE IN THE AREA WHERE IT IS BEING USED, IF THEY HAVE CHRONIC (LONG-TERM) LUNG OR BREATHING PROBLEMS OR IF THEY EVER HAD A REACTION TO ISOCYANATES.**

Use only with adequate ventilation.

Avoid contact with skin and eyes. Avoid breathing vapor and spray mist.

Wash hands after using.

This coating may contain materials classified as nuisance particulates (listed "as Dust" in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg/m<sup>3</sup> (total dust), 3 mg/m<sup>3</sup> (respirable fraction), OSHA PEL 15 mg/m<sup>3</sup> (total dust), 5 mg/m<sup>3</sup> (respirable fraction).

#### VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits.

Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

#### RESPIRATORY PROTECTION

Where overspray is present, a positive pressure air supplied respirator (TC19C NIOSH/MSHA approved) should be worn. If unavailable, a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2 may be effective. Follow respirator manufacturers directions for use. Wear the respirator for the whole time of spraying and until all vapors and mists are gone. **NO PERSONS SHOULD BE ALLOWED IN THE AREA WHERE THIS PRODUCT IS BEING USED UNLESS EQUIPPED WITH THE SAME RESPIRATOR PROTECTION RECOMMENDED FOR THE PAINTERS.**

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

**PROTECTIVE GLOVES**

To prevent skin contact, wear gloves which are recommended by glove supplier for protection against materials in Section 2.

**EYE PROTECTION**

Wear safety spectacles with unperforated sideshields.

**OTHER PROTECTIVE EQUIPMENT**

Use barrier cream on exposed skin.

**OTHER PRECAUTIONS**

This product must be mixed with other components before use. Before opening the packages, READ AND FOLLOW WARNING LABELS ON ALL COMPONENTS.

Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

## SECTION 9 — PHYSICAL AND CHEMICAL PROPERTIES

<b>PRODUCT WEIGHT</b>	7.96 lb/gal	954 g/l
<b>SPECIFIC GRAVITY</b>	0.96	
<b>BOILING POINT</b>	132 - 342° F	55 - 172° C
<b>MELTING POINT</b>	Not Available	
<b>VOLATILE VOLUME</b>	63%	
<b>EVAPORATION RATE</b>	Slower than ether	
<b>VAPOR DENSITY</b>	Heavier than air	
<b>SOLUBILITY IN WATER</b>	N.A.	
<b>VOLATILE ORGANIC COMPOUNDS (VOC Theoretical - As Packaged)</b>		
4.38lb/gal	526g/l	Less Water and Federally Exempt Solvents
4.12lb/gal	494g/l	Emitted VOC

## SECTION 10 — STABILITY AND REACTIVITY

**STABILITY — Stable****CONDITIONS TO AVOID**

None known.

**INCOMPATIBILITY**

None known.

**HAZARDOUS DECOMPOSITION PRODUCTS**

By fire: Carbon Dioxide, Carbon Monoxide

**HAZARDOUS POLYMERIZATION**

Will not occur

## SECTION 11 — TOXICOLOGICAL INFORMATION

**CHRONIC HEALTH HAZARDS**

No ingredient in this product is an IARC, NTP or OSHA listed carcinogen.

Methyl Ethyl Ketone may increase the nervous system effects of other solvents.

Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

**TOXICOLOGY DATA**

CAS No.	Ingredient Name			
67-64-1	Acetone	LC50 RAT	4HR	Not Available
		LD50 RAT		
78-93-3	Methyl Ethyl Ketone	LC50 RAT	4HR	Not Available
		LD50 RAT		
590-01-2	n-Butyl Propionate	LC50 RAT	4HR	Not Available
		LD50 RAT		
763-69-9	Ethyl 3-Ethoxypropionate	LC50 RAT	4HR	Not Available
		LD50 RAT		
123-86-4	n-Butyl Acetate	LC50 RAT	4HR	2000 ppm
		LD50 RAT		

## SECTION 12 — ECOLOGICAL INFORMATION

**ECOTOXICOLOGICAL INFORMATION**

No data available.

## SECTION 13 — DISPOSAL CONSIDERATIONS

### WASTE DISPOSAL METHOD

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers. Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

## SECTION 14 — TRANSPORT INFORMATION

### US Ground (DOT)

1 Gallon and Less may be Classed as CONSUMER COMMODITY, ORM-D  
Larger Containers are Regulated as:  
UN1263, PAINT, 3, PG II, (ERG#128)

### DOT (Dept of Transportation) Hazardous Substances & Reportable Quantities

n-Butyl acetate 5000 lb RQ

### Bulk Containers may be Shipped as (check reportable quantities):

UN1263, PAINT, 3, PG II, (ERG#128)

### Canada (TDG)

UN1263, PAINT, CLASS 3, PG II, (ERG#128)

### IMO

UN1263, PAINT, CLASS 3, PG II, (1 C c.c.), EmS F-E, S-E

## SECTION 15 — REGULATORY INFORMATION

### SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION

CAS No.	CHEMICAL/COMPOUND	% by WT	% Element
---------	-------------------	---------	-----------

No ingredients in this product are subject to SARA 313 (40 CFR 372.65C) Supplier Notification.

### CALIFORNIA PROPOSITION 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

### TSCA CERTIFICATION

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

## SECTION 16 — OTHER INFORMATION

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.