

Chemical Name: Childers cp-11 vl-cryl White

Manufacturer: Specialty Construction Inc.

Container size: 2 gallons

Location: VLA

Disposal: Place empty container in trash.

MATERIAL SAFETY DATA SHEET

REVISION DATE: 12-06-2007

SUPERSEDES: 12-29-2006

SECTION 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

COMPANY INFORMATION Specialty Construction Brands, Inc. An H.B. Fuller Company 1105 S. Frontenac Street Aurora, IL 60504 Phone: 1-800-323-7407

> Medical Emergency Phone Number (24 Hours): 1-888-853-1758 Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

PRODUCT INFORMATION PRODUCT IDENTIFIER: PRODUCT NUMBER: PRODUCT NAME: PRODUCT DESCRIPTION:

801800PM CP0110 CHILDERS CP-11 Coating

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

Unlisted ingredients are not 'hazardous' per the Occupational Safety and Health Administration Hazard Communication Standard (29 CFR 1910.1200) and/or are not found on the Canadian Workplace Hazardous Materials Information System ingredient disclosure list. See Section 8 for any additional exposure limit guidelines.

| Chemical Name | CAS # | PERCENT | OSHA PEL |
|--------------------|------------|---------|--|
| Crystalline silica | 14808-60-7 | 10 - 30 | TWA (Respirable dust) 0.1MG/M3 |
| Aluminum hydroxide | 21645-51-2 | 10 - 30 | TWA (as Al) Soluble 2MG/M3 |
| Titanium dioxide | 13463-67-7 | 1 - 5 | TWA (Total dust) 10MG/M3 |
| Cellulose | 9004-34-6 | 1 - 5 | TWA (Total dust) 15MG/M3 TWA (Respirable dust) 5MG/M3 |
| Vinyl acetate | 108-05-4 | 0.1 - 1 | TWA 10ppm STEL 20ppm |

SECTION 3: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW Cancer hazard. HMIS RATING: HEALTH -- 0 FLAMMABILITY -- 0 REACTIVITY -- 0 See SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for personal protective equipment recommendations.

POTENTIAL HEALTH EFFECTS BY ROUTE OF ENTRY EYE: Can cause minor irritation, tearing and reddening.

SKIN: Can cause minor skin irritation, defatting, and dermatitis.

INHALATION: Can cause minor respiratory irritation. Inhalation of dusts produced during cutting, grinding or sanding of this product may cause irritation of the respiratory tract.

Overexposure to crystalline silica may cause silicosis.

This product contains one or more materials that may be hazardous when present as an airborne dust. During normal handling of the product, the material is encapsulated within the product and will not present an exposure risk. Once the product has reached its final state and is abraded or disturbed, dusting and exposure may occur.

INGESTION: Ingestion is not an anticipated route of exposure. No hazard in normal industrial use.

LONG-TERM (CHRONIC) HEALTH EFFECTS TARGET ORGAN(S): Lungs

REGULATED CARCINOGEN STATUS:

Unless noted below, this product does not contain regulated levels of NTP, IARC, ACGIH, or OSHA listed carcinogens.

Crystalline silica Titanium dioxide Vinyl acetate

EXISTING HEALTH CONDITIONS AFFECTED BY EXPOSURE: Lung disease

SECTION 4: FIRST AID MEASURES

IF IN EYES: Use an eye wash to remove a chemical from your eye regardless of the level of hazard. Flush the affected eye for at least twenty minutes. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Seek medical advice after flushing.

IF ON SKIN: Wash with soap and water. Get medical attention if irritation develops or persists.

IF VAPORS INHALED: Remove to fresh air. Call a physician if symptoms persist.

IF SWALLOWED: Do not induce vomiting. Seek medical attention if symptoms develop. Provide medical care provider with this MSDS. Induced vomiting may lead to aspiration of the material into the lungs potentially causing chemical pneumonitis that may be fatal.

SECTION 5: FIRE FIGHTING MEASURES

| FLASH POINT: | Non flammable |
|-------------------------------------|---|
| AUTOIGNITION TEMPERATURE: | Not established |
| LOWER EXPLOSIVE LIMIT (% in air): | Not established |
| UPPER EXPLOSIVE LIMIT (% in air): | Not established |
| EXTINGUISHING MEDIA: | Use water spray, foam, dry chemical or carbon dioxide. |
| UNUSUAL FIRE AND EXPLOSION HAZARDS: | There is a possibility of pressure buildup in closed containers |
| | when heated. Water spray may be used to cool the containers. |
| SPECIAL FIRE FIGHTING INSTRUCTIONS: | Persons exposed to products of combustion should wear self- |
| | contained breathing apparatus and full protective equipment. |
| HAZARDOUS COMBUSTION PRODUCTS: | Carbon dioxide, Carbon monoxide |

SECTION 6: ACCIDENTAL RELEASE MEASURES

| SPECIAL PROTECTION: | No adverse health effects expected from the clean-up of spilled material. | |
|---------------------|--|--|
| | Follow personal protective equipment recommendations found in Section 8 | |
| | of this MSDS. | |
| CLEAN-UP: | Dike if necessary, contain spill with inert absorbent and transfer to containers | |
| | for disposal. Keep spilled product out of sewers, watersheds, or water | |
| | systems. | |

MATERIAL SAFETY DATA SHEET

Avoid creating dusts. Cover material with absorbent and moisten and collect for disposal.

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

SECTION 7: HANDLING AND STORAGE

Handling:No special handling instructions due to toxicity. Avoid breathing material.Storage:Store in a cool, dry place.

Consult the Technical Data Sheet for specific storage instructions.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

| EYE PROTECTION: | Wear safety glasses when handling this product. |
|-------------------------|--|
| SKIN PROTECTION: | Avoid skin contact by wearing chemically resistant gloves. |
| GLOVES: | Not normally required. Use nitrile gloves if conditions warrant. |
| RESPIRATORY PROTECTION: | Respiratory protection may be required to avoid overexposure when handling this product. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms. NIOSH approved air purifying respirator with dust/mist filter. Respirators should be selected by and used following requirements found in OSHA's respirator standard (29 CFR 1910.134). |
| VENTILATION: | Use local exhaust ventilation or other engineering controls to minimize exposures. |

EXPOSURE LIMITS:

| Chemical Name | ACGIH EXPOSURE LIMITS | AIHA WEEL | |
|--------------------|----------------------------------|-----------------|--|
| Crystalline silica | TWA (Respirable dust) 0.025MG/M3 | Not established | |
| Aluminum hydroxide | TWA (as Al) Soluble 2MG/M3 | Not established | |
| Titanium dioxide | TWA 10MG/M3 | Not established | |
| Cellulose | TWA (Total dust) 10MG/M3 | Not established | |
| Vinyl acetate | TWA 10ppm STEL 15ppm | Not established | |
| Vinyl acetate | | Not established | |

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

| PHYSICAL STATE: | Liquid |
|---------------------------|-----------------|
| COLOR: | White |
| ODOR: | Sweet |
| ODOR THRESHOLD: | Not established |
| WEIGHT PER GALLON (lbs.): | 11.3 |
| SPECIFIC GRAVITY: | 1.36 |

MATERIAL SAFETY DATA SHEET

SOLIDS (% by weight):

pH: BOILING POINT (deg. C): FREEZING/MELTING POINT (deg. C): VAPOR PRESSURE (mm Hg): VAPOR DENSITY: EVAPORATION RATE: OCTANOL/WATER COEFFICIENT: 63.7

Not established Not established Not established Not established Not established Not established

SECTION 10: STABILITY AND REACTIVITY

| STABILITY: | Stable under normal conditions. |
|-----------------------------------|---------------------------------|
| CHEMICAL INCOMPATIBILITY: | Not established |
| HAZARDOUS POLYMERIZATION: | Will not occur. |
| HAZARDOUS DECOMPOSITION PRODUCTS: | Carbon monoxide, carbon dioxide |

SECTION 11: TOXICOLOGICAL INFORMATION

| CHEMICAL NAME | LD50/LC50 |
|--------------------|--------------------------------------|
| Crystalline silica | Not established |
| | |
| Aluminum hudrovido | Not established |
| Aluminum hydroxide | Not established |
| | |
| Titanium dioxide | Not established |
| | |
| | |
| Cellulose | Oral LD50 Rat > 5g/kg |
| | Inhalation LC50 Rat > 5800mg/cu m/4H |
| | Dermal LD50 Rabbit > 2g/kg |
| Vinyl acetate | Oral LD50 Rat = 2920mg/kg |
| | Inhalation LC50 Rat = 11400ml/cu m |
| | Dermal LD50 Rabbit = 2335mg/kg |

TOXICOLOGY SUMMARY:

No additional health information available.

SECTION 12: ECOLOGICAL INFORMATION

OVERVIEW: No ecological information available

SECTION 13: DISPOSAL CONSIDERATIONS

To the best of our knowledge, this product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Solidify and dispose of in an approved landfill. Consult state, local or provincial authorities for more restrictive requirements.

SECTION 14: TRANSPORTATION INFORMATION

Consult Bill of Lading for transportation information.DOT:NOT REGULATEDIATA:NOT REGULATED

SECTION 15: REGULATORY INFORMATION

INVENTORY STATUS

U.S. EPA TSCA: This product is in compliance with the Toxic Substances Control Act's Inventory requirements.
CANADIAN CEPA DSL: This product is in compliance with the Canadian Domestic Substance List

requirements.

If you need more information about the inventory status of this product call 651-236-5858.

This product may contain chemical substances that are regulated for export by various government agencies (such as the Environmental Protection Agency, the Bureau of Industry and Security, or the Drug Enforcement Administration, among others). Before exporting this product from the USA or Canada, we recommend you contact us at 651-236-5858 (USA) or 450-655-1306 x227 (Canada) to request an export review.

FEDERAL REPORTING

EPA SARA Title III Section 313

Unless listed below, this product does not contain toxic chemical(s) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR part 372. EPA has advised that when a percentage range is listed the midpoint may be used to fulfill reporting obligations.

| Chemical Name | CAS# | % |
|---------------|----------|---------|
| Vinyl acetate | 108-05-4 | 0.1 - 1 |

WHMIS STATUS: Unless listed below, this product is not controlled under the Canadian Workplace Hazardous Materials Information System.

D2A

STATE REPORTING

This MSDS is not prepared for distribution in California.

SECTION 16: ADDITIONAL INFORMATION

This Material Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

Prepared by: The Global Regulatory Department Phone: 651-236-5842

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to Specialty Construction Brands, Inc. from its suppliers, and because Specialty Construction Brands, Inc. has no control over the conditions of handling and use, Specialty Construction Brands, Inc. makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and Specialty Construction Brands, Inc. assumes no responsibility for use or reliance thereon. It is the responsibility of the user of Specialty Construction Brands, Inc. products to comply with all applicable federal, state and local laws and regulations.