

Chemical Name: Cycle Chain Lube

Manufacturer: Gunk Liquid Wrench

Container size: 12oz.

Location: VLA

Disposal: Place empty container in trash.

MSDS No.: ML2S

I. Basic Information:

Manufacturer: RADIATOR SPECIALTY COMPANY Address: 600 RADIATOR ROAD City, ST Zip: INDIAN TRAIL, NC 28079 Country: Contact: Robert Geer Information Telephone Number: 704-684-1811 Emergency Contact: Rocky Mountain Poision Control Center Emergency Telephone Number: 303-623-5716 Emergency Restrictions:

Product Name: MOTORCYCLE, FARM & OUTDOOR POWER EQUIPMENT CYCLE CHAIN LUBE (UPC: 078698703060) MSDS No.: ML2S

Issue Date: 04/02/2008 Supersedes Date: 02/27/2008

II. Hazards Identification:

EMERGENCY OVERVIEW

Danger: Flammable, Harmful for fatal if swallowed, Vapor Harmful, Eye and Skin Irritant, Contents under pressure.

Level 3 Aerosol

OSHA Regulatory Status

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Potential Health Effects

Route(s) of Entry:

Eyes, skin, inhalation, ingestion

Health Hazards (Acute and Chronic):

See signs and symptoms below

Signs and Symptoms:

Eye Irritant. Skin irritation, defatting and dermatitis on prolonged exposure. Vapors harmful. May cause irritation to lungs, narcosis effects. Harmful if swallowed.

Medical Conditions Generally Aggravated by Exposure:

None known

Other Health Warnings:

Vomiting and subsequent aspiration into the lungs may lead to chemical pneumonia and pulmonary edema which is a potentially fatal condition.

Potential Environmental Effects

Not Available

III. Composition/Information on Ingredients:

Chemical Name	CAS No.	% Range	Trade Secret
1,2,4-Trimethylbenzene	95-63-6	1.0 - 5.0	
Aliphatic Hydrocarbon Solvent	8052-41-3	15.0 - 40.0	
Carbon dioxide	124-38-9	1.0 - 5.0	
Ethylene/Propylene Co-Polymer	25190-87-8	1.0 - 5.0	
Mesitylene	108-67-8	1.0 - 5.0	
Naphthenic Petroleum Distillate	64742-52-5	40.0 - 70.0	
Petroleum Lubricating Oil Base Stock	64742-18-3	7.0 - 13.0	
Xylene (mixed isomers)	1330-20-7	0.1 - 1.0	
Zinc Compound	19210-06-1	0.1 - 1.0	

MSDS No.: ML2S

IV. First Aid Measures:

Emergency and First Aid Procedures:

Eye Contact: Flush eyes with clean water for 15 minutes while lifting eyelids and get prompt medical attention.

Skin Contact: Wash with soap and water thoroughly. If adverse effects persist, get prompt medical attention. Launder contaminated clothing before reuse.

Inhalation: Remove to fresh air. If breathing becomes difficult get prompt medical attention.

Ingestion: DO NOT INDUCE VOMITING! Call Poison Control Center, physician, or hospital emergency room immediately.

Note to Physicians:

N/D

V. Fire Fighting Measures:

Suitable Extinguishing Media:

Water Fog, Foam, Carbon Dioxide, Dry Chemical

Unsuitable Extinguishing Media:

Do not use forced water stream as this could cause the fire to spread.

Products of Combustion:

Normal products of combustion: Carbon dioxide, carbon monoxide, smoke, nitrogen and sulfur oxides

Protection of Firefighters:

Wear self-contained positive pressure breathing apparatus and protective clothes. Use shield to protect from rupturing and venting containers. At elevated temperatures containers may vent, rupture or burst, even violently

VI. Accidental Release Measures:

Personal Precautions:

Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental Precautions:

Prevent run-off to sewers, streams, or other bodies of water. If run-off occurs, notify proper authorities as required that a spill has occurred. Run off to sewer may create fire or explosion hazard.

Methods for Containment:

Dike or contain spill and absorb with inert materials (sand, sawdust, absorbent sweeping compounds, rags, etc).

Methods for Cleanup:

Using a non-metalic scoop, place contaminated material into an approved chemical waste container. Where possible, vacuum spilled liquid using an explosion proof vacuum to recover material.

Other Information:

All equipment used with handling the concentrate must be grounded. If run-off occurs, notify proper authorities as required that a spill has occurred.

VII. Handling and Storage:

Handling Precautions:

Handling: Use with adequate ventilation and proper protective equipment. Do not use near fire, sparks, or flame. Do not puncture or incinerate container. Store in cool, well ventilated area below 120°F away from heat sources.

Storage Precautions:

Do not used in confined area without proper ventilation. Contact lenses may cause further damage in case of splash into eye. KEEP AWAY FROM CHILDREN AND ANIMALS!

VIII. Exposure Controls/Personal Protection:

MSDS No.: ML2S

Chemical Name	OSHA PEL	ACGIH TLV	Other Limits
Naphthenic Petroleum Distillate	5 mg/m3	5 mg/m3	Not Available
Aliphatic Hydrocarbon Solvent	100 ppm	100 ppm	NJ RTK
Petroleum Lubricating Oil Base Stock	N/E	N/E	Not Available
Ethylene/Propylene Co-Polymer	N/E	N/E	Not Available
1,2,4-Trimethylbenzene	N/E	25 ppm	Not Available
Mesitylene	N/A	N/A	Not Available
Xylene (mixed isomers)	100 ppm	100 ppm	Not Available
Zinc Compound	N/E	N/E	Not Available
Carbon dioxide	N/AV	5000 ppm	Not Available

Engineering Controls:

See Section 2 for applicable exposure limits. Use with adequate ventilation. If TLV is exceeded, wear NIOSH approved respirator.

Personal Protective Equipment:

For prolonged exposure wear protective safety glasses, gloves, and apron.

IX. Physical and Chemical Properties:

Boiling Point: 315°F Boiling Range: Not Available Solubility In Water: Insoluble Flash Point: 120°F Odor Threshold: Not Available Vapor Density (AIR = 1): N/D pH Range: Not Available Decomposition Temp: Not Available Lower Explosive Limit: N/D Specific Gravity (H20 = 1): 0.87 Other Information: N/D

Melting Point: N/A							
Freezing Point: Not Available							
Evaporation Rate (Butyl Acetate = 1): N/D							
Flash Point Method: TCC							
Appearance and Odor: Clear bright yellow with petroleum odor							
Vapor Pressure (mm Hg.): N/D							
Partition Coefficient: Not Available							
Auto-Ignition Temp: Not Available							
Upper Explosive Limit: N/D							

X. Stability and Reactivity:

Stability:

Stable

Conditions to Avoid:

See Incompatible Materials below.

Incompatible Materials:

Oxidizing agents and acids.

Hazardous Decomposition Products:

Normal products of combustion: Carbon dioxide, carbon monoxide, smoke, nitrogen and sulfur oxides

Possibility of Hazardous Reactions:

Will not occur

MSDS No.: ML2S

XI. Toxicological Information:

N/D

XII. Ecological Information:

N/D

XIII. Disposal Considerations:

DISPOSAL: This container may be recycled in aerosol recycling centers when empty. Before offering for recycling, empty the can by using the product according to the label. DO NOT PUNCTURE! If recycling is not available, wrap the container and discard in the trash. Dispose of unused product in accordance with all local, state government and federal laws and regulations.

XIV. Transport Information:

Shipping Name: Not Available

DOT Hazard Class: Not Available

UN/NA#: Not Available

Transportation Information: DOT Hazard Class: ORM-D Shipping Name: Consumer Commodity

DOT Subsidiary Hazard Class: Not Available Packing Group: Not Available

The DOT description is provided to assist in the proper shipping classification of this product and may not be suitable for international and air shipping purposes.

ICAO/IATA (US) Shipping Name: Aerosols Class: 2.1 UN number: UN1950

International:

ICAO/IATA UN number: UN1950 Shipping Name: Aerosols Class: 2.1

IMDG UN number: UN1950 Shipping Name: Aerosols Class: 2.1 EmS: F-D, S-U

XV. Regulatory Information:

SARA Reportable Chemicals.

USA TSCA: All components of this material are listed on the US TSCA Inventory.

Warning: This product contains a chemical(s) known to the State of California to cause cancer or birth defects or other reproductive harm.

SARA 313 Reportable Chemicals: 1,2,4-Trimethylbenzene (95-63-6) Xylene (1330-20-7) Zinc Dithiophosphate (19210-06-1)

MSDS No.: ML2S

XVI. Other Informate	ion:					
Chemical State:	X Liquid	Gas	Solid	NFPA	Fire	
Chemical Type:	Pure	X Mixture		Health	2 Reactivity	
Hazard Category:				1	0	
X Acute	X Chronic	X Fire				
	X Pressure	Reactive		×	Specjal	
Additional Manufacturer V	<u> Warnings:</u>				~	
Do not used in confined area without proper ventilation. Contact lenses may cause further damage in case of splash into eye. KEEP AWAY FROM		1	Health			
CHILDREN AND ANIMA				2	Flammability	
N/E: Not Established				0	Physical Hazard	
N/D: Not Determined				н	Pers. Protection	
N/A: Not Applicable N/AV: Not Available						
Additional Product Inform	nation:					

While Radiator Specialty Company believes this data is accurate as of the revision date, we make no warranty with respect to the data and we expressly disclaim all liability for reliance thereon. The data is offered solely for information, investigation, and verification. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this MSDS. The user is responsible for full compliance.