



**Chemical Name:** D' Gel Cable Gel Solvent

**Manufacturer:** LPS Laboratories

**Container Sizes:** 1 gal.

**Location:** VLA

**Disposal:** Place empty container in trash. Give partial or full container to safety officer.



# MATERIAL SAFETY DATA SHEET

## D'Gel Cable Solvent

Revision 5

Revision Date: 9/9/2009

Supersedes: 5/29/2008

### Section 1 • Product and Company Identification

**Product Name:** D'Gel Cable Gel Solvent

**Part Number:** 61244, 61202, 61232, 61296, 61201, 61255, C61244, C61232, C61201

**Chemical Name:** Hydrocarbon mixture

**Product Use:** A solvent agent designed for removing gels (icky-pic), blocking compounds, flooding and filling compounds from cables during splicing operations.

**Manufacturer Information:** LPS Laboratories, 4647 Hugh Howell Rd., Tucker, GA, USA 30084

**TEL:** 1 770-243-8880

**Emergency Telephone Number:** 1-800-424-9300 Chemtrec;  
Outside U.S.: (703) 527-3887

**FAX:** 1 770-243-8899

**Website:** <http://www.lpslabs.com>

### PLAIN LANGUAGE HAZARD SUMMARY

Material Safety Data Sheets can be confusing. Federal and State laws require us to include a great deal of technical information that probably will not help the non-professional. LPS includes this "PLAIN LANGUAGE HAZARD SUMMARY" to address the questions and concerns of the average worker. If you have additional health, safety or product questions, do not hesitate to call us at 800-241-8334.

#### Worker Toxicity

LPS D'GEL CABLE GEL SOLVENT is designed to remove grime, "icky-pic," and other contaminants from electrical and telecommunications cables during splicing operations. It contains d-limonene and isoparaffinic hydrocarbons that can be irritating to skin. We suggest you wear gloves and avoid extended exposure to unprotected skin. Do not get it in your eyes (it stings), or breath large amounts of the vapor, (it will dry out your nasal passages and if you breathe large amounts in poorly ventilated areas it can make you dizzy and even sick). Don't atomize LPS D'GEL CABLE GEL SOLVENT for extended periods without adequate ventilation. If you're going to perform work involving a lot of product in a poorly ventilated area, use of a respirator or even a self-contained breathing apparatus may be necessary. For more exposure and first aid information, refer to MSDS Sections 2, 8 and 11.

#### Flammability

LPS D'GEL CABLE GEL SOLVENT generates a "flame extension" when atomized into an ignition source (flame, arc, etc.), but in having a flash point above 141°F, it is generally safe to use for most industrial applications. Store product away from heat sources and do not spray into live electrical equipment.

#### Disposal

If you spill LPS D'GEL CABLE GEL SOLVENT, notify the proper environmental or safety department at your company right away. If LPS D'GEL CABLE GEL SOLVENT becomes contaminated with another substance and is rendered unusable for cleaning, the resulting mixture may fall under at least one hazardous classification.



# MATERIAL SAFETY DATA SHEET

## D'Gel Cable Solvent

Revision 5

Revision Date: 9/9/2009

Supersedes: 5/29/2008

---

### Section 2 • Hazards Identification

---

*This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).  
This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.*

**Emergency Overview:** CAUTION: Combustible liquid. Causes eye and skin irritation. May cause respiratory irritation. May cause drowsiness and dizziness. May be fatal if swallowed and enters airways.

**Primary route(s) of entry:** Skin and Eye contact. Inhalation.

**Potential Acute Health Effects:**

**Eyes** Irritating to eyes

**Skin** Repeated exposure may cause skin dryness or cracking.

**Inhalation:** Excessive inhalation of vapors can cause irritation of the respiratory tract, nausea, dizziness or headache.

**Ingestion:** Product has a low order of acute oral toxicity, but ingestion of large quantities may cause nausea, vomiting, and gastrointestinal irritation. May cause injury if aspirated into lungs.

**Potential Chronic Health Effects:**

**Carcinogenic Effects:** NTP: No IARC: No OSHA: No

**Mutagenic Effects:** None

**Teratogenic Effects:** None

**Medical conditions aggravated by exposure:** Persons with pre-existing central nervous system (CNS) disease, neurological conditions, skin disorders, chronic respiratory diseases, or impaired liver or kidney function should avoid exposure.

**Signs and Symptoms**

Stinging in eyes. Repeated or prolonged skin contact can cause redness, irritation, and scaling of the skin (dermatitis). Breathing of high vapor concentrations may cause headaches, stupor, irritation of throat and eyes, and kidney effects. Swallowing may cause vomiting which in turn can lead to aspiration into lungs.

---

### Section 3 • Composition / Information on Ingredients

---

Component	CASRN	Percent by Weight
Isoparaffinic Hydrocarbon	64742-48-9	70 - 90%
d-limonene	5989-27-5	10 - 20%



# MATERIAL SAFETY DATA SHEET

## D'Gel Cable Solvent

Revision 5

Revision Date: 9/9/2009

Supercedes: 5/29/2008

---

### Section 4 • First Aid Measures

---

- Eyes:** Check for and remove contact lenses. If irritation or redness develops, flush eyes with cool, clean, low pressure water for at least 15 minutes. Hold eyelids apart to ensure complete irrigation of the eye and eyelid tissue. Do not use eye ointment. Seek medical attention immediately.
- Skin:** Remove contaminated shoes and clothing. Clean affected area thoroughly with mild soap and water. Do not use ointments. Seek medical attention if irritation persists.
- Inhalation:** Immediately move victim to fresh air. If victim is not breathing, immediately begin rescue breathing. If heart has stopped, immediately begin cardiopulmonary resuscitation (CPR). If breathing is difficult, seek medical attention immediately.
- Ingestion:** Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If spontaneous vomiting is about to occur, place victim's head below knees. If victim is drowsy or unconscious, place on the left side with head down. Do not leave victim unattended. Seek medical attention immediately.

---

### Section 5 • Fire Fighting Measures

---

**Flash point:** TCC CLOSED CUP: 72°C (161°F) bulk liquid  
**Flammable limits:** LOWER: 1.3% UPPER: 8.9% **Auto ignition Temperature:** Not Established

**Products of Combustion:** Carbon monoxide and carbon dioxide.

**Firefighting media:** SMALL FIRE: Use DRY chemical powder.  
LARGE FIRE: Use water spray, fog or foam. Cool containing vessels with water jet in order to prevent pressure build-up, auto ignition or explosions.

**Sensitivity to Impact:** None. **Sensitivity to Static Discharge:** None.

**Protection Clothing (Fire):** Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies. Evacuate area and fight the fire from a maximum distance or use unmanned hose holders or monitor nozzles.

---

### Section 6 • Accidental Release Measures

---

- |                               |   |  |
|-------------------------------|---|--|
| <b>Containment Procedures</b> | <b>Small Spill and Leak:</b><br><b>Large Spill and Leak:</b>  | Eliminate ignition sources. Absorb with an inert material and dispose of properly.<br>Eliminate ignition sources, secure the area and control access. Dike far ahead of a liquid spill to ensure complete collection. Pick up free liquid for disposal using absorbent pads, sand, or other inert non-combustible absorbent materials. Place into appropriate waste containers for later disposal. |
| <b>Clean-Up Procedures</b>    | Recover free product and place in suitable container for disposal.                                    |  |
| <b>Evacuation Procedures</b>  | Ventilate area of leak or spill. Keep unnecessary and unprotected people away.                        |  |
| <b>Special Procedures</b>     | Remove all sources of ignition. Ventilate area. Wear appropriate protective equipment during cleanup. |  |



# MATERIAL SAFETY DATA SHEET

## D'Gel Cable Solvent

Revision 5

Revision Date: 9/9/2009

Supersedes: 5/29/2008

### Section 7 • Handling and Storage

**Handling:** DO NOT spray into or around ignition sources. Do not allow material to come into contact with eyes or skin.. Wear appropriate protective equipment during handling. After handling, always wash hands thoroughly with soap and water. Use only with adequate ventilation. Avoid breathing vapors or spray mists.

**Storage:** Keep container in a cool, well-ventilated area. Avoid all sources of ignition (spark or flame). Store below 120°F.

**Precautions to be taken in handling and storage:** Store all materials in dry, well-ventilated area. Avoid breathing vapors.

### Section 8 • Exposure Controls / Personal Protection

**Exposure Guidelines:**

Component	CASRN	OSHA TWA-PEL	OSHA STEL	ACGIH-TLV	ACGIH-STEEL	NIOSH REL
Isoparaffinic Hydrocarbon	64742-47-8	158 ppm Supplier RCP-TWA	Not Established	Not Established	Not Established	Not Established
d-limonene	5989-27-5	Not Established	Not Established	Not Established	Not Established	Not Established

**Engineering measures** Provide general and/or local exhaust ventilation to keep exposures below the exposure guidelines listed above.

**Personal protective equipment**

**Eye protection** Safety glasses with side shields conforming to appropriate regulations. Eye wash fountain and emergency shower facilities are recommended.

**Hand protection** If contact is likely, use chemical resistant gloves (i.e., nitrile, neoprene, buna) conforming to appropriate regulations. Please observe the instructions regarding permeability and breakthrough time that are provided by the supplier of the gloves.

**Respiratory protection** Typical use of this product under normal conditions does not require the use of respiratory protection. If airborne concentrations are above the applicable exposure limits (listed above), use NIOSH approved respiratory protection (i.e., organic vapor cartridge).

**General Hygiene Considerations** Wash thoroughly after handling. Have eye-wash facilities immediately available.



# MATERIAL SAFETY DATA SHEET

## D'Gel Cable Solvent

Revision 5

Revision Date: 9/9/2009

Supercedes: 5/29/2008

### Section 9 • Physical and Chemical Properties

<b>Appearance:</b>	Liquid.	<b>Color:</b>	Colorless / water-white
<b>Odor/Taste:</b>	Orange.	<b>pH:</b>	Not Applicable
<b>Solubility Description:</b>	Miscible at all proportions	<b>Evaporation Rate:</b>	<10 (BuAc=100)
<b>Boiling Point (°C):</b>	193°C (379 °F) @ 760mmHg	<b>Flash Point (°C):</b>	72°C (161°F)
<b>Specific Gravity (Water=1):</b>	0.78-0.80 @ 20 °C	<b>Flash Point Method:</b>	Tag-Closed Cup.
<b>Vapour Density (air=1):</b>	>1	<b>Auto Ignition Temperature (°C):</b>	Not Established
<b>Flammable limits (estimated):</b>	LOWER: 1.3% UPPER: 8.9%	<b>Partition Coefficient (octanol/water):</b>	<1
<b>Viscosity:</b>	<3 cSt @ 25°C	<b>Volatiles:</b>	97%

### Section 10 • Stability and Reactivity

<b>Chemical Stability:</b>	Product is stable under recommended storage conditions.
<b>Conditions to Avoid:</b>	Keep away from heat and ignition sources.
<b>Incompatibility:</b>	Extremely reactive or incompatible with oxidizing agents.
<b>Hazardous Decomposition:</b>	These products are carbon oxides (CO, CO <sub>2</sub> )
<b>Hazardous Polymerization:</b>	Will not occur.

### Section 11 • Toxicological Information

#### A: General Product Information

An acute toxicity study of this product has not been conducted. Information given in this section relates only to individual constituents contained in this preparation.

#### B: Component Analysis

Ingredients	CASRN	LC-50	LD-50
Isoparaffinic Hydrocarbon	64742-47-8	Not established	> 5000 mg/kg (oral, rat)
d-limonene	5989-27-5	Not established	>5000 mg/kg (oral, rabbit) >5000 mg/kg (dermal, rabbit)



# MATERIAL SAFETY DATA SHEET

## D'Gel Cable Solvent

Revision 5

Revision Date: 9/9/2009

Supercedes: 5/29/2008

---

### Section 12 • Ecological Information

---

**Mobility:** Semi-volatile. Readily absorbed into soil. **Persistence and degradability:** Only slightly biodegradable.

**Bioaccumulative potential:** No bioaccumulation potential **Other adverse effects:** None known.

#### Component Data: Acute Aquatic Toxicity

Component	CASRN	Test	Species	Results
Isoparaffinic Hydrocarbon	64742-47-8	Not Available		
d-limonene	5989-27-5	4-day LC <sub>50</sub>	Oncorhynchus mykiss	35,000 µg/L
		96-hour EC <sub>50</sub>	Pimephales promelas	1,490,000 µg/L

---

### Section 13 • Disposal Considerations

---

**Waste Status:** In its purchased form, this product is not classified as hazardous waste.

**Disposal:** Waste must be disposed of in accordance with federal, state and local environmental control regulations.

**Note:** Chemical additions to, processing of, or otherwise altering this material may make this waste management information inaccurate, incomplete, or otherwise inappropriate. Furthermore, state and local waste disposal requirements may be more restrictive than federal laws and regulations.

---

### Section 14 • Transport Information

---

This product is not regulated by any mode of transportation.



# MATERIAL SAFETY DATA SHEET

## D'Gel Cable Solvent

Revision 5

Revision Date: 9/9/2009

Supersedes: 5/29/2008

---

### Section 15 • Regulatory information

---

#### U.S. Federal Regulations

**RCRA Hazardous Waste No.:** None

**Comprehensive Environmental Response and Liability Act of 1980 (CERCLA):** None

**Toxic Substances Control Act (TSCA):**

All components of this product are TSCA inventory listed and/or are exempt.

**Superfund Amendments and Reauthorization Act (SARA) Title III**

**SARA Section 311/312 (40 CFR 370) Hazard Categories:**

Fire Hazard, Immediate (Acute) Health Hazard, Delayed (Chronic) Health Hazard

**This product contains the following toxic chemical(s) subject to reporting requirements of SARA Section 313 (40 CFR 372):**No individual section 313 component is present at or above 1%

**Section 112 Hazardous Air Pollutants (HAPs):** None

#### State Regulations

**New Jersey RTK:**

Isoparaffinic Hydrocarbon 64742-47-8 • d-limonene 5989-27-5 • Sodium Dioctyl Sulfosuccinate 577-11-7 • Glycols, polyethylene-polypropylene 9003-11-6

**California:** This product does not contain chemical(s) known to the State of California to cause cancer, birth defects or reproductive harm.

**California and OTC States:** This product is not regulated by consumer product regulations.

#### International Regulations

**Canadian Environmental Protection Act:** All of the components of this product are included on the Canadian Domestic Substances list (DSL).

**Canadian Workplace Hazardous Materials Information System (WHMIS):**

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

**WHMIS Classification:**

Class A, Class B5, Class D2B



#### Other Regulations

Montreal Protocol listed ingredients:	None.
Stockholm Convention listed ingredients:	None.
Rotterdam Convention listed ingredients:	None.
RoHS Compliant:	Yes.






# MATERIAL SAFETY DATA SHEET D'Gel Cable Solvent

Revision 5

Revision Date: 9/9/2009

Supersedes: 5/29/2008

## Section 16 • Other Information

MSDS# 161201 Responsible Name: Clea Johnson Regulatory Affairs Coordinator	HMIS 1996	HMIS III	<b>NFPA</b> Flammability  Health      1      2      0      Reactivity
	Health:            1	Health:            [ ]1	
	Flammability:    2	Flammability:    2	
	Reactivity        0	Physical Hazard   0	

### Notice to Reader:

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Clea Johnson, Regulatory Affairs Coordinator  
LPS Laboratories, A division of Illinois Tool Works