

Chemical Name: Magnaglo 14AM Prepared Bath

Manufacturer: Magnaflux

Container size: 228g

Location: VLA

Disposal: Place empty container in trash.

MAGNAGLO

MATERIAL SAFETY DATA SHEET MAGNAGLO® PREPARED BATH 14AM

IDENTIFICATION 1.

Company:	MAGNAFLUX
Address:	3624 West Lake Avenue, Glenview, Illinois 60026
Telephone No.:	847-657-5300 (Off-Hour Emergency Number - CHEMTREC - 1-800-424-9300).
Product Use:	Fluorescent magnetic particle inspection.
Packages:	5 gallon pail, aerosols.
NFPA Rating:	Health 1, Flammability 1 (aerosol 4), Reactivity 0
PIN (Canada):	None
Revision Date:	April 16, 2010

2. **HAZARDOUS INGREDIENTS**

<u>Ingredient</u>	<u>Wt./Wt. %</u>	<u>CAS #</u>	<u>TLV</u>	<u>PEL</u>	<u>LD₅₀</u>	<u>LC₅₀</u>
White mineral oil (petroleum)	60-100	8042-47-5	5 mg/mg	5 mg/mg	not avail.	not avail.
**Isobutane (propellant) **Aerosol only	30	75-28-5	not avail.	1000 ppm	not avail.	not avail.

HAZARDS IDENTIFICATION 3.

EMERGENCY OVERVIEW

Bland oily liquid which may irritate the skin. Difficult to ignite, but will burn vigorously if engulfed in fire. Aerosol is extremely flammable.

POTENTIAL HEALTH EFFECTS

Skin Contact:	May irritate by removing natural skin oils on long or repeated exposures.	
Eyes:	Possibly irritating.	
Inhalation:	Not significant. Isobutane vapors or heated bulk vapors may cause dizziness and nausea.	
Ingestion:	Not significant in small (mouthful) amounts.	
Medical conditions known to be aggravated by exposure to product: None		

FIRST AID 4.

Skin Contact: Wash off with soap and water. Use soothing lotion. Rinse carefully under upper and lower eyelids using plenty of water. Eyes: Inhalation: Remove to fresh air if dizzy or nauseated. Do not induce vomiting. Accidental ingestion of a single mouthful is not expected to cause significant harm. Ingestion: NOTE: In all severe cases, contact physician immediately. Local telephone operators can furnish number of regional poison control center.

FIRE HAZARD 5.

Conditions of flammability:	Bulk: Can ignite if heated above 200°F. Aerosol: Spraying near flames or arcs will ignite the spray mist.
Flash point (Bulk):	Minimum 200°F (93°C) (Pensky-Martens closed cup).
Flammable limits in air:	1% to 6%
Extinguishing media:	Carbon dioxide, foam.
Special fire fighting procedures:	Keep containers cool with water spray. Do not spray water on burning 14-AM. It will float and spread the fire.
Hazardous combustion products:	Smoke, soot, oxides of carbon.
Unusual fire hazards:	Aerosol cans may burst if heated above 130°F (54°C) and spray contents into a fire.

ACCIDENTAL RELEASE MEASURES 6.

Mop up or sweep up with absorbent. (For disposal, see Section 13.)

7. HANDLING AND STORAGE

Avoid breathing spray mist. Avoid repeated or prolonged skin contact. Avoid eye contact. Storage Level 3 Aerosols per NFPA 30B

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Controls: Personal protection: None, unless applied as spray. Use where ventilation will carry spray mist away from occupied areas. Wear nitrile rubber gloves if hand exposure is unavoidable. Respirator with filter if sprayed in enclosed, unventilated space.



A Division of Illinois Tool Works Inc. 3624 WEST LAKE AVENUE
GLENVIEW, ILLINOIS 60026 TEL 847.657.5300 FAX 847.657.5218 www.magnaflux.com

PHYSICAL PROPERTIES 9.

Initial boiling point (bulk):

VOC Content (EPA Method 24): Density/sp. gravity: Water solubility: pH:

Min. 455° F (235°C) (ASTM D-86)

795 g/L 0.82 0 Neutral

Vapor pressure:

Vapor density: Evaporation rate: Appearance: Odor:

Bulk: <0.10mm @ 70°F(21°C) Aerosol: 60 psi @ 75°F (24°C) Heavier than air Negligible Brown liquid Mild oily odor

10. STABILITY AND REACTIVITY

Stable Stability: Incompatibility: None Hazardous decomposition products: When burning, soot, carbon oxides. Reactivity: None

TOXICOLOGICAL INFORMATION 11.

Carcinogenicity: Threshold limit value: WHMIS information (Canada): Contains no known or suspected carcinogens listed with OSHA, IARC, NTP, or ACGIH. 5 mg/m for oily mist. According to available information, the ingredients have not been found to show reproductive toxicity, teratogenicity, mutagenicity, skin sensitization, or synergistic toxic effects with other materials.

ECOLOGICAL INFORMATION 12.

No data is available on 14AM. It floats on water and can be skimmed off. Its low bulk vapor pressure may exempt it from VOC restrictions. Isobutane is not an ozone depleter.

13. DISPOSAL

All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator.

TRANSPORTATION 14.

U.S. DOT: 49 CFR 172.101 Hazardous Materials Table

Proper shipping name: Hazard class or division: Identification No.: Packing Group:	<u>Bulk</u> None, not restricted None None None	<u>Aerosol</u> Consumer Commodity ORM-D None None
IATA: List of Dangerous Goods	<u>Bulk</u>	<u>Aerosol</u>
Proper shipping name:	None, not restricted	Aerosols, flammable
Hazard class or division:	None	2.1
Identification No.:	None	UN1950
Packing Group:	None	-
IMDG: General Index	<u>Bulk</u>	Aerosol
Proper shipping name:	None, not restricted	AEROSOLS
Hazard class or division:	None	2.1
Identification No.:	None	UN1950
Packing Group:	None	-

REGULATORY INFORMATION 15

TSCA: All ingredients are listed in TSCA inventory. CERCLA: Not reportable SARA TITLE III, Section 313: No reportable ingredients California Proposition 65: Contains nothing on this list WHMIS Class (Canada): Non-Aerosol: Not a controlled product. Aerosol: A, B-5. Note: This MSDS has been prepared to meet WHMIS (Canada) requirements with the exception of using 16 headings.

16. **OTHER INFORMATION**

Revision Statement:	Section 7
Supersedes:	MSDS dated 3/29/10
Prepared by:	Tamie Simmons, Research Manager



A Division of Illinois Tool Works Inc. 3624 WEST LAKE AVENUE
GLENVIEW, ILLINOIS 60026 TEL 847.657.5300 FAX 847.657.5218 www.magnaflux.com